



<b>Titre:</b> Title:	An Efficient Track-Scale Model for Laser Powder Bed Fusion Additive Manufacturing: Part 1- Thermal Model
Auteurs: Authors:	Reza Tangestani, Trevor Sabiston, Apratim Chakraborty, Waqas Muhammad, Yuan Lang, & Étienne Martin
Date:	2021
Туре:	Article de revue / Article
Référence: Citation:	Tangestani, R., Sabiston, T., Chakraborty, A., Muhammad, W., Lang, Y., & Martin, É. (2021). An Efficient Track-Scale Model for Laser Powder Bed Fusion Additive Manufacturing: Part 1- Thermal Model. Frontiers in Materials, 8, 753040 (14 pages). <u>https://doi.org/10.3389/fmats.2021.753040</u>

## **Document en libre accès dans PolyPublie** Open Access document in PolyPublie

## URL de PolyPublie: PolyPublie URL: https://publications.polymtl.ca/53239/

Tory Tublic Offe.	
Version:	Matériel supplémentaire / Supplementary material Révisé par les pairs / Refereed
Conditions d'utilisation: Terms of Use:	CC BY

Document publié chez l'éditeur officiel Document issued by the official publisher

<b>Titre de la revue:</b> Journal Title:	Frontiers in Materials (vol. 8)
Maison d'édition: Publisher:	Frontiers Media S.A.
URL officiel: Official URL:	https://doi.org/10.3389/fmats.2021.753040
Mention légale: Legal notice:	Copyright © 2021 Tangestani, Sabiston, Chakraborty, Muhammad, Yuan and Martin. This is an open-access article distributed under the terms of the Creative Commons Attribution License (CC BY). The use, distribution or reproduction in other forums is permitted, provided the original author(s) and the copyright owner(s) are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.

Ce fichier a été téléchargé à partir de PolyPublie, le dépôt institutionnel de Polytechnique Montréal This file has been downloaded from PolyPublie, the institutional repository of Polytechnique Montréal



## **Supplementary Material:**

As explained in the manuscript, the laser power-speed of 200 W-1000 mm/s was selected for calibration. **Figure I** shows the process of finding the optimum value of *C* for the HL model with  $\tau = 10$  as an example. Both models use identical meshes to compare the nodal temperatures. The HL model simulation was executed with values of *C* between 0.5 and 2 for the calibration coefficient. The enlarged section of **Figure 9** (except the gray section for the ED model) was selected to compare the results, which includes at least 1008 nodes (the second frame of **Figure I** has 1008 nodes as the gray section has its largest size). Then, each node was compared to find the average error between the ED and HL models. This process was repeated for each frame to find the average error for each frame. Next, the average error of all frames is calculated to evaluate the calibration coefficient. The calibration coefficient that produces the least error is used. Several different  $\tau$  values were evaluated to confirm the calibration coefficient is correct.



**FIGURE I** The algorithm to find the calibration coefficient for the HL model with  $\tau = 10$ .