

**Titre:** Structural stability of gravity dams: a progressive assessment  
Title: considering uncertainties in shear strength parameters

**Auteurs:** Mathilde Cordier, & Pierre Léger  
Authors:

**Date:** 2018

**Type:** Article de revue / Article

**Référence:** Cordier, M., & Léger, P. (2018). Structural stability of gravity dams: a progressive assessment considering uncertainties in shear strength parameters. Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards, 12(2), 109-122. <https://doi.org/10.1080/17499518.2017.1395464>  
Citation:

## Document en libre accès dans PolyPublie

Open Access document in PolyPublie

**URL de PolyPublie:** <https://publications.polymtl.ca/5615/>  
PolyPublie URL:

**Version:** Version finale avant publication / Accepted version  
Révisé par les pairs / Refereed

**Conditions d'utilisation:** Tous droits réservés / All rights reserved  
Terms of Use:

## Document publié chez l'éditeur officiel


Document issued by the official publisher

**Titre de la revue:** Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards (vol. 12, no. 2)  
Journal Title:

**Maison d'édition:** Taylor & Francis  
Publisher:

**URL officiel:** <https://doi.org/10.1080/17499518.2017.1395464>  
Official URL:

**Mention légale:** This is an Accepted Manuscript of an article published by Taylor & Francis in Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards (vol. 12, no. 2) in 2018, available online: <https://doi.org/10.1080/17499518.2017.1395464>  
Legal notice:



**Structural stability of gravity dams: a progressive assessment considering uncertainties in shear strength parameters**

Journal:	<i>Georisk</i>
Manuscript ID	NGRK-2017-0020.R1
Manuscript Type:	Original Article
Date Submitted by the Author:	n/a
Complete List of Authors:	Cordier, Mathilde; Ecole Polytechnique de Montreal Departement des Genies Civil Geologique et des Mines Leger, Pierre; Ecole Polytechnique de Montreal Departement des Genies Civil Geologique et des Mines,
Keywords:	dam safety, uncertainty, factor of safety, reliability analysis, Monte Carlo simulation

SCHOLARONE™  
Manuscripts

**Abstract**

Structural sliding stability of gravity dams is most often quantified using a binary safe/unsafe criterion such that the shear resistance has to be larger than the driving shear load. Large deterministic factors of safety,  $FS_{det}$  (e.g. 3 in normal condition), are used in existing guidelines to guard against material and loads uncertainties. Some guidelines allow an arbitrary reduction in  $FS_{det}$  (e.g. 2) when the knowledge in strength parameters increases from material test data. Yet, those reduced  $FS_{det}$  are not based on a rational consideration of uncertainties. Propagation of uncertainties could be done using comprehensive probabilistic analyses, such as Monte-Carlo simulations (MC). However, MC are complex and challenging for practical use. There is thus a need to develop simplified reliability based safety assessment procedures that could rationalise the adjustment of  $FS_{det}$  from existing dam safety guidelines. This paper presents a progressive analysis methodology using four existing safety evaluation formats of increasing complexity: (i) deterministic, (ii) semi-probabilistic (partial coefficient), (iii) reliability based *Adjustable Factor of Safety (AFS)*, and (iv) probabilistic (MC). Comprehensive comparisons are made for the sliding safety evaluation of a 80 m gravity dam. Results are presented in terms of sliding factors of safety, allowable water levels, and demand/capacity (load and resistance) ratios. It is shown that the reliability based AFS formulation, using direct integration, is simple and practical to use in complement to existing dam safety guidelines before undertaking MC simulations. AFS yielded results with a maximum difference of approximately 10% as compared to rigorous MC probabilistic analyses.

## 1. Introduction

Dams are major infrastructures, for which failure is an extremely rare event but with very serious consequences. Gravity dams are particularly sensitive to overtopping, due to the large hydrostatic thrust and uplift pressures that reduce the shear strength capacity that could be mobilised by frictional resistance and cohesion along lift joints or the concrete-rock interface. Dams have a useful service life extending for decades, such that aging of materials and the magnitude of anticipated floods evolve with advances in predictive methodologies and changes in the environment. The structural stability of major dams needs to be re-evaluated every 5-10 years according to Hazard Classification Systems (HCS), most often within the legal framework of a governmental regulatory agency.

Structural stability against sliding should satisfy a binary safe/unsafe limit-state stating that the shear resistance,  $R$ , has to be strictly larger than or equal to the driving shear load,  $L$ . To guard against uncertainties in  $R$  and  $L$ , large deterministic factors of safety ( $FS_{det}$ ) are used. These large  $FS_{det}$  may be reduced when new knowledge about the material shear strength parameters is acquired to better quantify the friction coefficient and cohesion. For instance, in CDA (2007),  $FS_{det} = 3$  if no material test is available, and  $FS_{det} = 2$  if tests are done. A better knowledge of strength parameters thus authorises a reduced safety margin. However, the specified  $FS_{det}$  numerical values are rounded numbers from experience and not from a rational approach to quantify reduction in strength parameters uncertainties.

There is thus a need to develop, validate and verify simplified reliability based safety assessment procedures that could rationalise the  $FS_{det}$  adjustment by referring to data bases developed from evaluating  $L$  and  $R$  uncertainties readily available from countless test series and load statistics (Kreuzer and Léger 2013). Simplified methods should be robust,

1  
2  
3 computationally efficient, with a limited number of random variables, and easily  
4  
5 interpretable. They then can replace the deterministic L and R parameters. Moreover,  
6  
7 reliability based safety assessment will also answer a societal aspect in form of relating the  
8  
9 required safety margin to a HCS used by the dam safety regulations of the particular  
10  
11 country. Of course, comprehensive reliability based probabilistic analyses could be  
12  
13 undertaken to propagate uncertainties in structural stability analyses. However,  
14  
15 comprehensive probabilistic analyses (e.g. Monte Carlo (MC) simulations) require  
16  
17 extensive time, sophisticated tools, expertise and resources that are most often not  
18  
19 available. To adjust the required safety margin as a function of a reduction in shear strength  
20  
21 uncertainties, this paper presents a progressive analysis methodology of increasing  
22  
23 complexity and accuracy. It consists in applying successively (i) deterministic analyses,  
24  
25 (ii) simplified reliability based *Adjustable Factor of Safety (AFS)* analyses, and (iii) full  
26  
27 probabilistic analyses (crude MC). The main objective of the paper is to establish the range  
28  
29 of AFS modelling parameters for which coherent results could obtained with MC  
30  
31 simulations that are used as reference values.  
32  
33  
34  
35  
36  
37

38  
39 This paper is organised as follows. After the review of literature in section 2, section 3  
40  
41 describes four different safety formats: (i) deterministic, (ii) semi-probabilistic (partial  
42  
43 coefficient), (iii) reliability based AFS, and (iv) probabilistic (MC). Comprehensive  
44  
45 comparisons of the four safety evaluation formats are done by comparing sliding stability  
46  
47 indicators of a 80 m-high gravity dam, studied in a previous ICOLD numerical Benchmark  
48  
49 seeking to quantify the sliding probability of failure,  $p_f$ , as a function of the upstream  
50  
51 reservoir water elevation,  $H_w$  (Escuder-Bueno et al., 2011). It is shown that coherent results,  
52  
53 as compared to MC, could be obtained while using the AFS method when the required  
54  
55  
56  
57  
58  
59  
60

safety margin is being compared to the ratio of resistance and load mean values. The AFS method is thus shown as a simple and practical preliminary substitute to full probabilistic MC analysis that may therefore be avoided within the scope of the gravity dam stability problem studied herein. Two additional AFS safety margin formulations have also been investigated to demonstrated its range of applicability as compared to MC (i) when all uncertainties have been factored in AFS parameters such that  $AFS \geq 1$ , and (ii) when an additional safety margin is deemed necessary to account for ignorance, or lack of information in spite of having considered uncertainties with all AFS factors (Kreuzer and Leger 2013).

## 2. Stability assessment of gravity dams considering uncertainty analysis

One can solve the gravity dam stability problem as a deterministic one where there is no uncertainty. At the other end of the spectrum, total ignorance of phenomena that may affect stability, and its outcome, cannot be quantified because classification and identification of what is unknown is not possible (Riley, Webley and Thomson 2017; D. Rumsfeld famous deep "*unknown-unknown*" uncertainty; Baecher 2016). We will therefore focus our analysis on epistemic and aleatory uncertainties in input data (friction coefficient and cohesion) that admit statistical descriptions from a frequentist point of view.

***Deterministic analysis*** is traditionally used to assess the stability of dams (ANCOLD 2013; CDA 2007; FERC 2002; Ruggeri 2004; USBR 1976; USACE 1995, 2005). Deterministic methods do not allow accounting explicitly for uncertainties in strength capacity and load effects (stresses). Moreover, deterministic FSs are round numbers without rational safety-relevant significance, apart from grading them to the frequency of load combination (usual,

unusual, extreme). There is thus a huge interest in the profession to move towards more refined methods to consider uncertainties.

*Probabilistic analysis* allows considering nature's randomness, and human incomplete knowledge within the probabilistic safety evaluation. Mathematical constructs are used normally presented by probability density functions and engineering judgment. Then, comparisons between several failure scenarios are possible while assessing probability of failure,  $p_f$ , and related risk according to the consequence model. Probabilistic methods are thus very useful tool to decision-making (Bury and Kreuzer 1985; FERC 2014). Probabilistic risk analysis, and associated risk management, are used for other civil structures and are now in active development in dam engineering (Baecher 2016; FERC 2014; Hartford and Baecher 2004; Hartford et al. 2016; Kalinina et al. 2016; Peyras et al. 2010; Peyras et al. 2012; SPANCOLD 2013; Westberg Wilde and Johansson 2016; Zhang et al. 2016). As dam engineering is moving towards models accounting for uncertainties, ICOLD organized an International Benchmark Workshop on Numerical Analysis of Dams in 2011 to examine probabilistic analysis (Escuder-Bueno et al., 2011). A new ICOLD Benchmark on Risk Assessment took place in 2017 (Johansson et al. 2017). Risk assessment uses probabilistic methods, and consists (i) to combine failure modes to determine a failure scenario by using event or failure trees, (ii) to model failure modes, (iii) to assess the failure probability for each failure mode, (iv) to deduce the total dam failure probabilities. The concept of "*As Low As Reasonably Possible (ALARP)*" is then used in several dam safety guidelines to answer the difficult question "*How safe is safe enough?*" (Bowles 2007). ALARP is used to accept or reject the resulting failure probability and related consequences. Recognising that absolute safety cannot be achieved, the

1  
2  
3 mathematical concept of risk is used to specify reasonable efforts to avert losses  
4  
5 considering what can be achieved with the available resources. Reasoning in terms of  
6  
7 probability of failure and acceptable risks is a key societal construct, subjected to time  
8  
9 evolution. While accepting the ALARP principle, it is then possible to make the transition  
10  
11 between the deterministic world, where achieving the required  $FS_{det}$  is believed to provide  
12  
13 absolute safety, and the probabilistic world where uncertainties are explicitly recognised  
14  
15 (Luhmann 2005).  
16  
17

18  
19 A probabilistic analysis could account for uncertainties in cohesion, friction, drain  
20  
21 efficiency, and several other parameters as shown in Altarejos-Garcia et al. (2015, 2012).  
22  
23 Probabilistic analysis also allows reliability assessment of dam-foundation-reservoir  
24  
25 systems (Westberg Wilde and Johansson 2013). In reliability based safety assessment,  
26  
27 fragility analysis, first used in seismic evaluation of nuclear power plants, is a key step  
28  
29 (Porter 2017). Fragility analysis is the computation of the probability to reach an  
30  
31 undesirable limit-state for a known loading intensity. Fragility curves, expressed as  
32  
33 function of reservoir elevation,  $H_w$ , provide quantitative cumulative distribution functions  
34  
35 for the dam to resist sliding. Fragility curves provides a rational tool that could be used to  
36  
37 compare several remedial options if a need for strengthening is identified (Ebeling et al.  
38  
39 2012; Ellingwood and Tekie 2001; Tekie 2002).  
40  
41  
42  
43  
44

45  
46 However, probabilistic assessments require many parameters to describe uncertainties,  
47  
48 such as random variables, Probability Density Functions (PDF), PDF bounds, coefficients  
49  
50 of variation, which may affect substantially the analysis results as shown by the wide  
51  
52 dispersion in fragility curves computed from the participants in the ICOLD Benchmark  
53  
54 (Escuder-Bueno et al. 2016). Then, the decision to take remedial action, if necessary,  
55  
56  
57  
58  
59  
60



depends on a complex and possibly not unique assessment: one may wonder about limits of reliability methods, which are finally not the unerring reference (Kreuzer 2000, 2003).

*Semi-probabilistic (partial coefficient) analysis* is a first simplified approach that allows considering uncertainties according to each load and resistance parameter (ANCOLD 1991; CFBR 2013, 2015; IS 1984-1998; Peyras et al. 2008; Rocha 1974; SPANCOLD 2003). Partial safety coefficients are ideally calibrated according to probabilistic analyses. However, each dam is a unique hydro-geomechanical system. Calibration may not be based on consistent sampling, but adapted to correspond to existing structures designed with deterministic methods (Jongejan and Calle 2013; Kovarik 2000). In the Netherlands, the National Flood Risk Analysis project developed recommendations evolving from deterministic to semi-probabilistic analysis to assess stability of hydraulic structures (levees), using probabilistic analysis to calibrate coefficients according to target failure probability,  $p_r^*$  (Jongejan and Maaskant 2013; Vergouwe 2016).

*Adjustable Factor of Safety (AFS)* analysis is another simplified and practical way to perform probabilistically (reliability) based safety assessment. AFS considers only two basic random variables, the resistance  $R$  and the load,  $L$ . AFS is seeking a binary outcome such that  $AFS \geq FS_{req}$ , where  $FS_{req}$  is depending on a user defined target  $p_r^*$  or a target reliability index,  $\beta^*$ . As described in more details in section 3, AFS connects  $R$  and  $L$  within a probabilistic framework using their PDF along with six uncertainty factors calibrated on empirical evidences, including coefficients of variations as well as upper (for  $L$ ) or lower (for  $R$ ) PDF bounds (Kreuzer and Léger 2013).

1  
2  
3 A progressive approach, with increasing level of complexity to assess the sliding stability  
4 of gravity dams is therefore proposed as follows: (i) deterministic analysis is done first, (ii)  
5 then semi-probabilistic method can optionally be used to distinguish uncertainties about  
6 the friction coefficient and cohesion. (iii) The AFS method is next performed to rationally  
7 adjust the computed  $FS_{det}$  and compared it to  $FS_{req}$  considering a probabilistic description  
8 of  $R$  uncertainties and a selected target  $p_f^*$  or  $\beta^*$ . Finally, (iv) full probabilistic analysis  
9 may be undertaken if deemed necessary.  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19

### 20 21 22 23 **3. Specification for required safety margins in investigated safety evaluation formats**

#### 24 25 26 **3.1 Deterministic**

27  
28 Deterministic analysis is traditionally used to design and assess dam stability. It consists in  
29 defining a factor of safety (FS) between the dam's resistance  $R$  and the loading  $L$  from  
30  $FS = R/L$ , and to compare it to required values according to applicable guidelines. The  
31 gravity method and Mohr-Coulomb criterion are most often employed to define the shear  
32 strength resistance to compute sliding FS. Typically, three values for resistance are  
33 considered in parametric study: best estimate, lower bound, and upper bound. Different  
34 load combinations are considered, only those associated with water levels are studied  
35 herein: usual, unusual, and extreme (flood). Moreover, required FS relate to dam-  
36 foundation interface and lift joints.  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49

50 Some guidelines require FS without any consideration to the level of knowledge about  
51 strength parameters (Table 1). Some other guidelines recommend FS considering the level  
52 of knowledge in strength parameters. The required FS are larger if no material tests have  
53 been realised (Table 2).  
54  
55  
56  
57  
58  
59  
60

Table 1. Required deterministic factors of safety without any explicit consideration of uncertainties.

Load combination	Required factor of safety		
	UBSR (1976)	USACE (1995)	FERC (2002) <sup>(a)(b)</sup>
Usual	3.0	2.0	3.0
Unusual	2.0	1.7	2.0
Extreme	1.0	1.3	-

<sup>(a)</sup> Dams are categorised according to the consequences of a failure: the coefficients are for a dam with moderate to high risks.  
<sup>(b)</sup> Other FS are required for friction only (cohesion is null).

Table 2. Required deterministic factors of safety depending on the level of knowledge of strength parameters.

Load combination	Required factor of safety					
	CDA (2007) <sup>(a)</sup>		ANCOLD (2013) <sup>(a)</sup>		USACE (2005) <sup>(b)</sup>	
Knowledge?	No tests	With tests	Not well-defined <sup>(c)</sup>	Well-defined <sup>(c)</sup>	Well-defined <sup>(d)</sup>	Ordinary
Usual	3.0	2.0	3.0	2.0	2.0	1.7
Unusual	2.0	1.5	2.0	1.5	1.5	1.3
Extreme	1.3	1.1	1.5	1.3	1.1	1.1

<sup>(a)</sup> Other FS are required for friction only (CDA 2007) or residual values for C,  $\tan\phi$  (ANCOLD 2013).  
<sup>(b)</sup> Dams are categorised according to the consequences of a failure: the FS are for a dam with moderate to high risks.  
<sup>(c)</sup> According to ANCOLD (2013), "well-defined" means that "a sufficient number of tests have been done to specify the strength parameters with reasonable certainty (e.g. assumed strength is exceeded by 80% of the test results from a test regime involving a significant number of tests)".  
<sup>(d)</sup> According to USACE (2005), site information is "well-defined" when records are available, dam is monitored, uplift are known, and "foundation strengths can be established with a high level of confidence".

3.2 Semi-probabilistic (partial coefficients)

Rocha (1974) suggested to introduce partial safety coefficients for friction and cohesion instead of a single FS. This approach is to account for different levels of uncertainties in these two shear strength mechanisms. Divisor coefficients of 1.5 to 2, and 3 to 5, could be applied respectively to the friction coefficient,  $\tan\phi$ , and the cohesion, C. It is thus recognised that uncertainties in cohesion are more important than in friction, whereas there

is no mathematical justification for the recommended values. Thereafter, countries like India (IS 1984-1998) and Spain (SPANCOLD 2003) chose to use the concept of partial strength reduction coefficients (Table 3).

Semi-probabilistic assessment consists in using some partial safety coefficients for both loads and strengths, increasing loads and reducing strengths depending on the target reliability of the structural component. These coefficients are ideally calibrated from probabilistic methods, and adapted to existing structures designed with deterministic analysis (Jongejan and Calle 2013; Kovarik 2000).

Table 3. Semi-probabilistic partial safety coefficients

Load combination	Partial safety coefficients							
	IS (1984-1998)		SPANCOLD (2003) <sup>(b)</sup>		CFBR (2013)		ANCOLD (1991) <sup>(c)</sup>	
	$\gamma_C$ <sup>(a)</sup>	$\gamma_{\tan\phi}$	$\gamma_C$	$\gamma_{\tan\phi}$	$\gamma_C$	$\gamma_{\tan\phi}$	Strength	Load <sup>(d)</sup>
Usual	3.6	1.5	5.0	1.5	3.0	1.5	0.3	
Unusual	3.6	1.5	4.0	1.2	2.0	1.2	0.4	
Extreme – flood	1.2	1.0	3.0	> 1.0	1.0	1.0	0.8	

<sup>(a)</sup> C is the cohesion,  $\tan\phi$  is the friction coefficient;  $\gamma_C$  and  $\gamma_{\tan\phi}$  are associated partial safety coefficients such that semi-probabilistic sliding stability limit-state criterion is:  $\frac{A_c \cdot C / \gamma_C + V \cdot \tan\phi / \gamma_{\tan\phi}}{L} > 1.0$  where V is the sum of vertical forces,  $A_c$  the compressed sliding area, L the hydrostatic thrust (IS 1984-1998; SPANCOLD 2003; CFBR 2013).

<sup>(b)</sup> Dams are categorised according to the consequences of failure: the coefficients are for a dam with moderate to high risks.

<sup>(c)</sup> Multiplier coefficients applied to strength and load parameters to compute  $R'$  and  $L'$  such that semi-probabilistic sliding stability limit-state criterion is:  $R' > L'$  (ANCOLD 1991).

<sup>(d)</sup> Coefficients for loads are 0.95 for water and well-known dead loads contributing to stability, 0.90 for not well-known concrete weight, 1.05 for water, uplift and dead loads contributing to instability, 1.50 for live and silt loads contributing to instability.

### 3.3 Probabilistic

Deterministic FS and partial safety coefficients do not inform about the safety margin including uncertainties about parameters employed in analysis. Probabilistic analysis allows to compute a failure probability,  $p_f$ , considering mathematically uncertainties. HCS have been developed to differentiate structures according to the consequences a failure.

The ALARP concept has often been used to link loss of human lives (or persons in danger), more than material costs of consequences, to recommended acceptable failure probability (Figure 1).




Figure 1. Concept of "As Low As Reasonably Possible" adapted from (CDA 2007).

In probabilistic analysis, load (L) and resistance (R) parameters are statistically distributed according to PDF selected to be representative of tests and knowledge about these parameters. Failure develops when internal load demand exceeds the resistance capacity of the dam. Influences of different selections of PDF data in probabilistic analyses have been studied in Altarejos-Garcia et al. (2012); Carjaval et al. (2009a, 2009b, 2009c); Carjaval, Peyras, and Baconnet (2010); Krounis and Johansson (2012); Krounis et al. (2016); Lombardi (1988, 1993, 2006); Spross, Johansson and Larsson (2013). Probabilistic analysis, no matter how sophisticated, can still lead to very different solutions for a given problem because of the complex choices of random variables, characteristic values, PDF, bounds, which can largely influence final results. For example, Figure 2 illustrates the wide dispersion obtained from participants in an ICOLD Benchmark seeking to compute the

fragility curve (Fcurve) for  $p_f$  as a function of  $H_w$  for a 80 m-high gravity dam given fifteen sets of "cohesion, friction angle" data pair representing material test data. The detailed description of the problem is given in section 4.1 of this paper. In Figure 2, we present results from all participants that used MC simulations, (Fcurves 1-7) as well as our own MC solutions (Fcurves 8-12). Using the same PDF data for  $C$  and  $\tan\phi$ , ICOLD Fcurve 2 is similar to Fcurve 8 computed herein for water levels ranging from 75 m to 80 m. Our MC probabilistic analysis procedure is thus validated for the selected PDF data.




Figure 2. Dispersion in fragility curves computed for the ICOLD Benchmark for a 80 m-high gravity dam (Fig. 5);  $\phi$  is the friction angle,  $C$  the cohesion,  $R$  the global resistance of the dam defined in Eq. 2;  $N$  = normal distribution,  $LN$  = lognormal distribution; selected bounds are indicated. Fcurves1 to 7 are from participants in the ICOLD Benchmark, Fcurves 8 to 12 are our solutions to the Benchmark.

3.4 Reliability based Adjustable Factors of Safety: AFS

Kreuzer and Léger (2013) presented a simplified reliability based method to assess dam stability. It depends on two uncertain random variables, R and L. An *Adjustable Factor of Safety (AFS)* is defined by:

$$AFS = \frac{\mu_R \{1 - (k_R \cdot c_R + \alpha_R)\}}{\mu_L \{1 + (k_L \cdot c_L + \alpha_L)\}} = FS_{det} \cdot U_{RL} \quad (Eq. 1)$$

$FS_{det}$  is the deterministic factor of safety,  $c_R$  and  $c_L$  are the coefficients of variation related to physical uncertainties, the natural intrinsic dispersion of values,  $k_R$  and  $k_L$  are related to statistical uncertainties defined herein as the lack of knowledge, from the number and reliability of material test data and  $\alpha_R$  and  $\alpha_L$  are related to model or (epistemic) uncertainties (Figure 3). Comprehensive description and numerical values for these coefficients have been suggested in Kreuzer and Léger (2013) depending on the knowledge of the structure.

Considering only two random variables, R and L, the AFS aims to be compared to a Required Safety Factor,  $FS_{req}$ , depending on a target failure probability,  $p_f^*$ , or the corresponding reliability index  $\beta^*$ . For a safe structure, the stability criterion becomes  $AFS \geq FS_{req}$ .  $FS_{req}$  is computed iteratively by direct integration to be the  $FS = \mu_R/\mu_L$  such that with the selected PDF data for R and L, the computed  $p_f$  would correspond to the target failure probability,  $p_f^*$ . PDF are bounded at distances from the mean corresponding to a number  $k_R$  or  $k_L$  of standard deviations, on the left for the resistance and on the right for the load. For unbounded PDF, tails of distributions are considered in the computation of  $FS_{req}$  (it would correspond to  $k = \infty$ ), but a  $k$  value has to be defined for the computation of AFS.  $FS_{req}$  decreases when the uncertainties in L and R are reduced. The AFS is a simple



approach to introduce uncertainties using PDF data of the basic random variables  $\mathbf{L}$  and  $\mathbf{R}$  directly into the safety evaluation process. It allows to study the effect of reducing the coefficient of variation of the resistance,  $c_R$ , using material tests, on a rational basis as opposed to existing deterministic dam safety guidelines using arbitrary reduced FS requirements. The AFS considers only  $p_f^*$ , that could be specified directly from a HCS, avoiding to rely on assessing speculative terms of risk which require a complementary loss model. A user-friendly open source computer program, **R-AFS**, was developed to perform AFS and  $FS_{req}$  computations (Morin 2016). The R-AFS implementation is controlled by an input-output environment, using the "**R**" open-source statistical computational platform (see <https://www.r-project.org/>). A copy of R-AFS could be obtained by contacting the second author (pierre.leger@polymtl.ca).




Figure 3. Definition of the six uncertainty coefficients in the reliability-based AFS format: (i)  $c_R = \sigma_R/\mu_R$ , (ii)  $k_R$ , (iii)  $\alpha_R$ , (iv)  $c_L = \sigma_L/\mu_L$ , (v)  $k_L$ , (vi)  $\alpha_L$ .

The advantages of the reliability-based AFS are (i) the rationality to account for uncertainties using selected PDF data and a target  $p_f^*$  (or  $\beta^*$ ) in similarity to probabilistic analysis, (ii) its simplicity and practical use, (iii) a clear interpretation in the form of a binary decision to accept/reject the computed FS.

Of course, if one has the certitude to have properly factored all uncertainties with the  $c$ ,  $k$  and  $\alpha$  values,  $FS_{req} = 1$  would be adequate. The general accepted safety performance



1  
2  
3 criterion then becomes  $AFS \geq 1$ . Another approach is to consider all uncertainties in the  
4  
5 computation of  $FS_{req}$ . In the gravity dam shear strength problem, we are then seeking to  
6  
7 satisfy  $(\mu_R/\mu_L) \geq FS_{req}(c_R, k_R, \alpha_R, p_f^*)$ . However, an additional safety margin might be  
8  
9 provided for initial imperfection, ignorance or lack of information leading to the acceptance  
10  
11 criterion  $AFS \geq FS_{req}(c_R, k_R, \alpha_R, p_f^*)$  (Kreuzer and Léger 2013). These three acceptance  
12  
13 criteria (i)  $AFS \geq 1$ , (ii)  $(\mu_R/\mu_L) \geq FS_{req}$ , and (iii)  $AFS \geq FS_{req}$  are compared with MC  
14  
15 analyses, used as the reference solution to evaluate the reliability based AFS method.  
16  
17  
18  
19

20  
21  
22  
23 3.5 Progressive approach to introduce uncertainties  
24

25  
26 The above safety evaluation formats, ranging from deterministic to comprehensive  
27  
28 probabilistic analyses, show different ways to account for uncertainties, from various  
29  
30 sources appearing at each level of the stability assessment of the dam: material testing,  
31  
32 selection of strength and load parameters, structural model. A progressive approach may  
33  
34 then be developed to best account for these uncertainties, from simple to more complex but  
35  
36 more precise evaluation formats (Figure 4).  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60




Figure 4. Progressive approach for dam safety assessment: parameters, sources of uncertainties and performance indicators.

## 4. Application of progressive safety assessment

### 4.1 Description of the gravity dam for applications

The dam for applications is a 80 m-high concrete gravity dam that might be subjected to overtopping. The dam geometry (Figure 5) is given in the 11th ICOLD Numerical Benchmark (Escuder-Bueno et al., 2011). A single and simple failure mode, corresponding to horizontal sliding along the dam-foundation interface, is to be investigated. In reality, the kinematic of a dam base sliding-turning failure mode might occur along inclined planes propagating in the foundation (Fishman 2009). However, our study is restricted to the ICOLD benchmark problem to allow comparisons with previously published results (Fig. 2). The resistance, **R**, is a function of two basic random variables, (i) the friction

coefficient,  $\tan\phi$ , and (ii) the cohesion,  $C$ . The dam weight,  $W$ , and the drain effectiveness,  $E$ , are considered as given constant parameters. The uplift pressure,  $U$ , is a function of the water level,  $H_w$ . In this application, there is no uncertainty for the load,  $L$ . The water level,  $H_w$ , is increased systematically to reach an unacceptable limit state. In the case of overtopping, the water weight on the crest is estimated as  $W_w$ . The gravitational acceleration, the dam-foundation interface tensile strength, the water and concrete densities used in computations are respectively,  $g = 9.81 \text{ m/s}^2$ ,  $f_t = 0$ ,  $\rho_w = 1000 \text{ kg/m}^3$ , and  $\rho_c = 2400 \text{ kg/m}^3$ . The classical gravity method is used in stability analyses, considering cracking at the dam-foundation interface. If the base crack extends beyond the drain, the full uplift pressure is considered in the crack.




Figure 5. Geometry, load, L, drainage, and resistance, R, (friction and cohesion) properties of the gravity dam analysed.

Fifteen couples of friction angle  $\phi$  ( $^{\circ}$ ) and cohesion  $C$  (kPa) are specified as input "material test" data in the 11th ICOLD Numerical Benchmark seeking to estimate the sliding probability of failure,  $p_f$ , of the dam (see Appendix 1). The statistics for  $C$  and the friction coefficient,  $\tan\phi$ , are summarised in Table 4. The coefficient of variation for cohesion,  $c_c$ , is 0.67, which is quite large. Distribution fitting has been realised with N-PDF and LN-PDF. The LN-PDF was found to suit the data best taking into account the skewness, whereas N-PDF is symmetrical.

Table 4. Material test data statistics for friction and cohesion at the dam-foundation interface.

Material test	Cohesion C (kPa)	Friction angle $\phi$ (°)	Friction coefficient $\tan\phi$
Mean $\mu$ – best estimate	367	52.4	1.36
Standard deviation $\sigma$	247	7.99	0.39
Coefficient of variation c	0.67	0.15	0.29
Minimum – lower bound	0	37	0.75
Maximum – upper bound	800	63	1.96
5% fractile – N	0	39.3	0.72
5% fractile – LN	112	40.3	0.82

4.2 Deterministic stability evaluation

Deterministic analyses are first realised with mean values selected as best estimates for cohesion, C, and friction coefficient,  $\tan\phi$ . Smallest and largest values are taken as lower and higher bounds. For the usual and unusual load combinations, the maximal allowable water level,  $H_w$ , is computed according to CDA (2007, Table 2), without and with material tests (Figure 6).




Figure 6. Maximum allowable water level according to deterministic CDA (2007) dam safety guidelines.

These results indicated the importance of having a good knowledge of shear strength parameters. For the usual load combination, the allowable water level increased by 10 m if material tests are realised. However, CDA (2007) does not provide clear guidance on the number of tests, the sampling location and the testing method to be used to obtain representative results with a quantified confidence level. ANCOLD (2013) suggests criteria for the "well-defined" material shear strength parameters (Table 2).

#### 4.3 Probabilistic safety evaluation using Monte-Carlo simulations

A probabilistic assessment requires to select a target  $p_f^*$ , random variables, their PDF, and their bounds if they are bounded. PDF are bounded at distances from the mean corresponding to a number  $m$  of standard deviations on the left and on the right. Unbounded PDF corresponds to  $m = \infty$ . Herein, the  $p_f^*$  is  $10^{-5}$ , consistent with the ALARP principles for a high-risk dam (CDA 2007). We work with two sets of random variables either  $(C, \tan\phi)$  or  $R$ . The resistance,  $R$ , is described as the sum a friction and a cohesion component:

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

$$R = V \cdot \tan\phi + A_c \cdot C \quad (\text{Eq. 2})$$

a mean value is computed for R and the standard deviation,  $\sigma_R$ , is estimated from:

$$\sigma_R = \sqrt{(V \cdot \sigma_{\tan\phi})^2 + (A_c \cdot \sigma_C)^2} \quad (\text{Eq. 3})$$

where V is the sum of vertical forces, and  $A_c$  the area in compression.

The related PDF are successively selected as N and LN in sensitivity analyses. Bounded and unbounded PDF are also studied. MC computations are realised with MATLAB® (The MathWorks 2016),  $n = 10^7$  samples are found adequate to obtain convergence for  $p_f$ . For instance, when  $p_f = 10^{-5}$ , the accuracy is  $p_f = 10^{-5} \pm 5 \cdot 10^{-7}$ .

**Unbounded PDF** are first studied. When the unbounded hypothesis is considered with N-PDF, negative values of C,  $\tan\phi$ , or R, are replaced by new draws in MC simulations. The results are presented in Figure 7. LN-PDF yielded failure probabilities smaller than N-PDF. The reduction from two random variables, (C,  $\tan\phi$ ), to one random variable, R, gave similar  $H_w$  results.




Figure 7. Fragility curves comparing **unbounded** N-PDF and LN-PDF, variables (C,  $\tan\phi$ ) or R, computed with MC; and  $H_w$  according to probabilistic analysis for a target failure probability  $p_f^* = 10^{-5}$ .

The effect of **bounded PDF** is investigated by selecting values between the 5% fractile for strength parameters on the left of the distribution:  $m_l$  standard deviations, and the 95% fractile on the right:  $m_r$  standard deviations (Figure 8). For variables C,  $\tan\phi$ , R,  $m_l$  are respectively equal to 1.03, 1.38, 1.39 and  $m_r$  respectively equal to 1.88, 1.84, 1.83.






Figure 8. Fragility curves comparing **bounded** N-PDF and LN-PDF at the 5% and 95% fractile values, variables (C,  $\tan\phi$ ) or R, computed with MC; and maximum allowable water level according to probabilistic analysis for a  $p_i^* = 10^{-5}$ .

Results were similar using N-PDF or LN-PDF, but more sensitive to the selection of random variables. Using a single random variable, R, instead of two (C,  $\tan\phi$ ), yielded higher  $H_w$ .

#### 4.4 Semi-probabilistic (partial coefficient) stability evaluation

For the semi-probabilistic analysis, CFBR (2013) suggests as characteristic values, a "wise estimation of the mean", and the 5% fractile if statistical methods are used. Herein, two pairs of (C,  $\tan\phi$ ) are used (i) mean values as best estimates (367, 1.36), and (ii) 5% fractile obtained from the 15 material test data assuming a N-PDF (0, 0.72, Table 4) considered in typical user of CFBR. The partial strength safety coefficients are applied for the usual, unusual, and extreme load combinations (Table 3).

With the extreme combination, the computed  $H_w$  was 106 m using the mean values for ( $C$ ,  $\tan\phi$ ), but as complete base cracking occurred at **104 m** we used this last value as the maximum  $H_w$ . Allowable  $H_w$  according to each load combination are presented in Figure 9.




Figure 9. Maximum allowable water level according to semi-probabilistic CFBR (2013) dam safety guidelines.

These results showed a very significant sensitivity of the semi-probabilistic method to the selected characteristic values.

#### 4.5 Reliability based Adjustable Safety Factors – AFS

The selected  $p_r^*$  is  $10^{-5}$  as recommended for a high-risk dam with good quality assurance and management (Kreuzer and Léger 2013). The AFS method is employed without uncertainties in load  $L$ ,  $c_L = 0$ , also, coefficients reporting model uncertainties  $\alpha_R$  and  $\alpha_L$ .

are null. The shear strength random variable in the AFS method is  $R$ . The related PDF is LN as recommended in Kreuzer and Léger (2013).

**Unbounded PDF** are first studied. Tails of distributions are considered while computing  $FS_{req}$  but a value for  $k_R$  has to be defined for the evaluation of AFS. Values selected for  $k_R$  in the AFS computation (Eq. 1) are (i)  $k_R = 1.39$ , corresponding to the 5% fractile for  $R$  for LN-PDF (Holický 2009), (ii)  $k_R = 2$ , (iii)  $k_R = 3$ .  $FS_{req}$  is computed with unbounded PDF. Computed AFS and  $FS_{req}$  are presented in Figure 10. For  $k_R = 3$ , allowable water level was less than 40 m.




Figure 10. AFS method: deterministic  $FS_{det}$ ; required  $FS_{req}$  for  $p_f^* = 10^{-5}$  and **unbounded** LN-PDF for  $R$ ; and AFS for (i)  $k_R = 1.39$ , (ii)  $k_R = 2$ , (iii)  $k_R = 3$ .

For **bounded PDF** the effect of bounds is investigated by selecting (i)  $k_R = 1.39$  (corresponding to the 5% fractile for  $R$  for our LN-PDF (Holický 2009), (ii)  $k_R = 2$ , and (iii)  $k_R = 3$  for the computation of AFS as well as  $FS_{req}$ . The computed AFS and  $FS_{req}$  are presented in Figure 11. For  $k_R = 3$ ,  $H_w$  was again less than 40 m.




Figure 11. AFS method: deterministic safety factor  $FS_{det}$ ; required safety factor  $FS_{req}$  for  $p_f^* = 10^{-5}$  and **bounded** LN-PDF for R; AFS and  $FS_{req}$  for (i)  $k_R = 1.39$ , (ii)  $k_R = 2$ , (iii)  $k_R = 3$ .

## 5. Discussion

### 5.1 Results from different safety evaluation formats

The 80 m dam was analysed according to four safety evaluation formats applying the proposed progressive safety assessment methodology. The key results are presented (i) in Figure 6 for deterministic analyses, (ii) in Figure 9 for semi-probabilistic analyses, (iii) in Figures 10-11 for AFS, and (iv) in Figures 7-8 for probabilistic MC analyses. Comparative  $H_w$  results are presented in Figure 12. Table 5 presents the computed FS for each safety format that are compared to the required FS to declare a safe dam. The reference value to make comparisons and orient the discussion is  $H_w = 90$  m. This allowable  $H_w$  is computed from MC simulations, using  $C$  and  $\tan\phi$  as random variables, with LN-bounded PDF

( $m_l = 1.03$  for  $C$  and  $1.38$  for  $\tan\phi$ , corresponding to the 5% fractile). It is a reasonable and defensible probabilistic model having considered strength uncertainty in a rational way with two random variables, as well as existing dam safety guidelines to select PDF bounds. Obviously, other reference value for  $H_w$  could be selected. However, we present coherent hypotheses moving from one level of complexity to the next such that meaningful comparisons and discussion could be established.

The *deterministic* format criteria (Table 2, CDA 2007) are unable to consider the large coefficient of variation in shear strength parameters,  $H_w$  being **102 m** for extreme conditions (flood) if material tests had been realised. A parametric analysis showed that lower bound of shear strength data would authorise  $H_w$  equal to **82 m**.

*Probabilistic* sensitivity analyses were applied with random variables ( $C$ ,  $\tan\phi$ ) or  $R$ , LN-PDF, and unbounded or bounded distributions, with  $p_r^* = 10^{-5}$ . For the unbounded case,  $H_w$  was **76 m** with variables ( $C$ ,  $\tan\phi$ ) and **75 m** with variable  $R$ , leading to similar results. With bounds corresponding to the 5% fractiles for strength parameters,  $H_w$  was **90 m** (the reference value) for variables ( $C$ ,  $\tan\phi$ ) and **94 m** for  $R$ . Probabilistic analysis (MC) may be considered as the most rigorous approach but is shown to be sensitive to the selection of random variables and PDF bounds.

In *semi-probabilistic analysis*, two pairs of values for ( $C$ ,  $\tan\phi$ ) were used. For the extreme combination, using the mean,  $H_w$  was **104 m**. Using the 5% fractile,  $H_w$  was **83 m**. This 83 m value was the same as using bounded N-PDF with variables ( $C$ ,  $\tan\phi$ ) in probabilistic analysis (Figure 8), meaning that calibration of partial coefficients in semi-probabilistic analysis appears to be consistent with results of N-PDF bounded probabilistic analysis.

The *reliability-based adjustable safety factors (AFS)* with criterion " $AFS \geq FS_{req}$ " yielded very low  $H_w$  for unbounded LN-PDF. For unbounded PDF,  $H_w$  values were very sensitive to the coefficient  $k_R$ . It is deemed inadequate in our application.

The criterion " $AFS \geq 1$ " gave the same  $H_w$  for unbounded and bounded LN-PDF because this criterion is not related to the computation of  $FS_{req}$ , using PDF data. For  $k_R = 1.39$  and  $k_R = 2$ ,  $H_w$  obtained with the criterion " $AFS \geq 1$ " are the same as those obtained with criterion " $(\mu_R/\mu_L) \geq FS_{req}$ ". The criterion " $(\mu_R/\mu_L) \geq FS_{req}$ " gave the same  $H_w$  for unbounded PDF even for  $k_R = 3$ . This means that bounding PDF with large  $k_R$  is equivalent in ~~RBSF~~ **AFS** to consider the whole content of the distribution.

## 5.2 Comparisons of different safety evaluation formats

For the same 80 m gravity dam stability problem, with known 15 pairs  $(C, \tan\phi)$  and considering (i) no uncertainty, (ii) uncertainties believed to be known with certainty either in RBSF or probabilistic analysis or, (iii) uncertainties with an added safety margin, may decrease the allowable  $H_w$  from 104 m to 60 m (Figure 12). Table 5 presents FS computed by each safety evaluation format and the associated safety criterion for two water levels: 80 m and 90 m. Demand/capacity ratios  $(D/C)$  have been computed in each case as  $(H_w^2/90^2)$  because the applied hydrostatic thrust,  $L$ , could be estimated as  $L = (\rho_w g H_w^2)/2$ .  $D/C$  ratios are presented in enclosed boxes in Figure 12, and for varying values of PDF bounds,  $m_l$  (MC) and  $k_R$  (AFS), in Figure 13.




Figure 12. Maximum allowable water level for different safety formats: (i) deterministic, (ii) semi-probabilistic, (iii) AFS criterion " $AFS \geq FS_{req}$ ", (iv) AFS criterion " $(\mu_R/\mu_L) \geq FS_{req}$ ", (v) probabilistic MC simulations with random variables  $(C, \tan\phi)$ , (vi) probabilistic MC simulations with random variable  $R$ . LN-PDF is used for AFS and probabilistic methods. In boxes are Demand/Capacity ratios.

Table 5. Sliding FS from safety formats: (i) deterministic (CDA 2007), (ii) semi-probabilistic (CFBR 2013), (iii) three criteria of AFS method, (iv) probabilistic (MC simulations).

	80 m - unusual		90 m - extreme	
<b>Deterministic</b>	FS <sub>det</sub>	FS <sub>det</sub> <sup>req</sup>	FS <sub>det</sub>	FS <sub>det</sub> <sup>req</sup>
FS <sub>det</sub> ≥ FS <sub>det</sub> <sup>req</sup>	2.84	≥ 1.5	1.86	≥ 1.1
<b>Semi-prob.</b>	FS' <sub>unus</sub>	FS' <sub>req</sub>	FS' <sub>extr</sub>	FS' <sub>req</sub>
FS' ≥ FS' <sub>req</sub>	2.14	≥ 1.0	1.86	≥ 1.0
<b>ASF</b> <sup>(a)</sup>	AFS	AFS <sup>req</sup>	AFS	AFS <sup>req</sup>
(i) AFS ≥ 1	1.77	≥ 1.0	1.17	≥ 1.0
	μ <sub>R</sub> /μ <sub>L</sub>	FS <sub>req</sub>	μ <sub>R</sub> /μ <sub>L</sub>	FS <sub>req</sub>
(ii)	2.84	≥ 1.61	1.86	≥ 1.58
(μ <sub>R</sub> /μ <sub>L</sub> ) ≥ FS <sub>req</sub>				
	AFS	FS <sub>req</sub>	AFS	FS <sub>req</sub>
(iii)	1.77	≥ 1.61	1.17	< 1.58
AFS ≥ FS <sub>req</sub>				
<b>Probabilistic</b> <sup>(b)</sup>	FS <sub>pr</sub>	FS <sub>pr</sub> <sup>req</sup>	FS <sub>pr</sub>	FS <sub>pr</sub> <sup>req</sup>
FS <sub>pr</sub> ≥ FS <sub>pr</sub> <sup>req</sup>	1.26	≥ 1.0	1.0	≥ 1.0

<sup>(a)</sup> AFS computations with bounded PDF and  $k_R = 1.39$ .

<sup>(b)</sup> Reference value from probabilistic analyses is 90 m. FS<sub>pr</sub> is defined by the inverse of the demand/capacity ratio.

Deterministic and semi-probabilistic formats do not allow to account for uncertainties in parameters used for computations. The allowable  $H_w$  were especially high using mean values as strength parameters (102 m and 104 m an allowable capacity approximately 30% larger than the reference value). Using lower bound or 5% fractile values as strength parameters in a sensitivity analysis yielded much smaller  $H_w$  (82 m and 83 m), because of the large scatter in test data.

Application of AFS method (computation of FS<sub>req</sub> and AFS) allows to quantify uncertainties in the safety evaluation. Comparing (μ<sub>R</sub>/μ<sub>L</sub>) to FS<sub>req</sub> is then a mathematically expressible safe/unsafe criterion. Allowable  $H_w$  were 94 m and 86 m for bounded PDF with  $k_R$  respectively equal to 1.39 and 2. This criterion yielded the same  $H_w$  as probabilistic MC



simulations using variable R and bounded at 5% fractile. This is because direct integration used in computation of  $FS_{req}$  and MC simulations give the same  $p_f$ . While using  $(\mu_R/\mu_L) \geq FS_{req}$ ,  $H_w$  is 94 m corresponding to a D/C of 1.1 using the 90 m reference value. A maximum difference of 10%, as compared to the reference solution, is deemed acceptable for a simplified method. This difference decreases while increasing the PDF bound such that AFS is found to have the same range of applicability as that of MC with a maximum difference of the order of 10%. The criterion " $AFS \geq 1$ " gave also 94 m and 86 m for bounded PDF and  $k_R$  equal to 1.39 and 2, respectively. The range of applicability of the criterion " $AFS \geq 1$ " is indicated in terms of D/C ratios in Figure 13. If we accept a difference of 10% with the reference solution, the use of " $AFS \geq 1$ " is restricted to  $k_R$  value smaller than 2.5. On the other hand, comparing AFS to  $FS_{req}$  allows to introduce an additional safety margin. This added safety margin obviously yields to significantly lower allowable  $H_w$  and smaller D/C ratios as compared to other safety formats.




Figure 13. Demand/Capacity ratios for AFS as compared to MC, for varying PDF bounds in MC simulations ( $m_l$ ) and AFS ( $k_R$ )

From a practical standpoint, we feel confident to allow  $H_w$  equal to 83 m (3 m of overtopping) for the ICOLD Benchmark dam, using the " $AFS \geq FS_{req}$ " criterion with  $k_R = 1.39$  corresponding to the 5% fractile of the shear strength parameters. After performing the "sophisticated" analyses presented in this paper, we checked our findings from McCann et al. (1985) against rules of thumb for the allowable depth of overtopping,  $h_o$ , as a function of the dam height, using  $h = 80$  m (262.4 ft), in our case. Preliminary screening values for  $h_o$  are based on field experience and engineering judgement. They were recommended using the following description and equations (in feet) (i) for dams in good condition: with very little seepage, no cracks or movement ( $h_o = h^{0.6} \approx 8.6$  m), (ii) for dams in a fair condition: with moderate seepage, small structural cracks, slight differential movement ( $h_o = h^{0.45} - 1 \approx 3.5$  m) and (iii) for dams in poor conditions: with excessive seepage, large continuous cracks, excessive differential movements ( $h_o = h^{0.3} - 1 \approx 1$  m). The proposed " $AFS \geq FS_{req}$ " criterion yielded a  $h_o$  value of 3 m corresponding to the rule of thumb for a dam in fair condition. This sounds about right considering the potential scour at the downstream toe, the vibrations induced by the overflowing aerated water nappe, the increased in downstream toe uplift pressure due to the downstream face water jet changing direction at the toe. Such phenomenon are not being considered explicitly in dam safety guidelines, and are very difficult to model from a sound probabilistic standpoint.

## 6. Conclusions

In this paper, the consideration of material uncertainties in gravity dam sliding stability assessment was investigated for four safety evaluation formats: (i) deterministic, (ii) semi-

probabilistic (partial coefficient), (iii) reliability-based Adjustable Factor of Safety (AFS), and (iv) probabilistic Monte Carlo (MC) analysis. The results were presented in terms of the allowable water level,  $H_w$ , demand/capacity ratios (D/C), and FS to reach an unstable condition. In AFS and MC, the selected target failure probability,  $p_f^*$ , was  $10^{-5}$ . A 80 m-high gravity dam was used for applications without considering uncertainties in the applied loads,  $L$ . The main conclusions can be summarised as follows:

- The dam engineering profession shows a huge interest in comprehensive probabilistic methods. However, computation of  $p_f$  is very sensitive to the selection of shear strength random variables and PDF data as shown by the wide dispersion observed from the ICOLD Benchmark's results for a 80 m-high gravity dam. Practical applications are thus challenging, and generalisation of probabilistic analyses needs clear guidance.
- Using the deterministic format,  $H_w$  was found to be 103 m as compared to a reference MC solution with  $H_w$  equal to 90 m. The Deterministic safety format was found inadequate to introduce uncertainties even with an arbitrary reduction of the required FS if material tests are conducted
- In MC analyses, PDF bound data are the predominant parameters affecting the computation of  $p_f$ . A simplified bounded MC solution, using a single force resultant shear strength random variable,  $R$ , yielded a dam capacity approximately 10% larger than a bounded reference MC solution using two random variables (cohesion,  $C$  and friction,  $\tan\phi$ ). This excessive capacity decreases as the PDF bound becomes larger, the difference becoming insignificant when unbounded distributions are considered.
- A reliability-based adjustable safety factor (AFS) is a simplified and practical approach to introduce probabilistic uncertainties in shear strength parameters. The criterion

" $(\mu_R/\mu_L) \geq FS_{req}$ ", using direct integration to compute  $FS_{req}$ , yielded the same results as MC simulations using the same PDF data and a single random variable, R. This criterion is recommended as a preliminary substitute to full probabilistic MC analysis that may therefore be avoided within the scope of the gravity dam stability problem studied herein. The proposed simplified approach yields a good accuracy with a 10% maximum difference with respect to a more comprehensive MC reference solution. The criterion " $AFS \geq FS_{req}$ ", which introduces an additional safety margin, cannot be compared the MC reference solution, because no additional safety margin was introduced in the MC solution. " $AFS \geq FS_{req}$ " yielded a lower allowable water level (83 m) than the MC solution (90 m). However,  $H_w = 83$  m does correspond to an established rule of thumb to estimate the capacity of a 80 m-high gravity dam.

- The proposed AFS method is a practical answer to the need for a simplified and robust method to introduce material data shear strength uncertainties using a rigorous approach in gravity dam stability analysis. Its range of applicability and the adequacy of the safety margin provided as compared to reference MC solutions make ~~RBSF~~ **AFS** a useful tool to use in sensitivity analysis of PDF data before undertaking more comprehensive MC analyses (or variants such as FORM).

## Acknowledgements

The financial support provided by the Natural Science and Engineering Research Council of Canada is acknowledged. The authors would also like to thank Dr Harald Kreuzer for proposing the AFS and the fruitful technical discussions that took place during this study.

References

Altarejos-Garcia, L., Escuder-Bueno, I., and Morales-Torres, A. (2015). "Advances on the failure analysis of the dam-foundation interface of concrete dams." *Materials*, 8, 8255-8278.

Altarejos-Garcia, L., Escuder-Bueno, I., Serrano-Lombillo, A., and Membrillera-Ortuño, G. D. (2012). "Methodology for estimating the probability of failure by sliding in concrete gravity dams in the context of risk analysis." *Structural Safety*, 36-37, 1-13.

ANCOLD. (2013). *Guidelines on design criteria for concrete gravity dams*. Australia: Australian National Committee on Large Dams.

ANCOLD. (1991). *Guidelines on design criteria for concrete gravity dams*. Australia: ANCOLD.

Baecher, G. B. (2016). "Uncertainty in dam safety risk analysis." *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*, 10(2), 92-108.

Bowles, D. S. (2007). "Tolerable risk for dams: How safe is safe enough?" Paper presented at the 27<sup>th</sup> US Society on Dams Annual Conference, Philadelphia, USA.

Bury, K. V., and Kreuzer, H. (1985). "Assessing the failure probability of gravity dams." *Water Power & Dam Construction*, 37(11), 46-50.

Carjaval, C., Peyras, L., Arnaud, P., Boissier, D., and Royet, P. (2009a). "Assessment of hydraulic load acting on dams including filling variability and stochastic simulations." *European Journal of Environmental and Civil Engineering*, 13(4), 399-411.

Carjaval, C., Peyras, L., Arnaud, P., Boissier, D., and Royet, P. (2009b). "Probabilistic modeling of floodwater level for dam reservoirs." *Journal of Hydrologic Engineering*, 14(3), 223-232.

Carjaval, C., Peyras, L., and Bacconnet, C. (2010). "On the loading/shear strength coupling in the probabilistic formulation of the limit-state in shear for gravity dams." *European Journal of Environmental and Civil Engineering*, 14(3), 283-301.

Carjaval, C., Peyras, L., Bacconnet, C., and Bécue, J.-P. (2009c). "Probability modelling of shear strength parameters of RCC gravity dams for reliability analysis of structural safety." *European Journal of Environmental and Civil Engineering*, 13(1), 91-119.

CDA. (2007). *Dam safety guidelines*. Edmonton, Canada: Canadian Dam Association.

CFBR. (2013). *Recommendations for the justification of the stability of gravity dams*. France: Comité Français des Barrages et Réservoirs.

CFBR. (2015). *Guidelines for the justification of embankment dams and levees*. France: CFBR.

Ebeling, R. M., Fong, M. T., Wibowo, J. L., and Chase, A. (2012). *Fragility analysis of a concrete gravity dam embedded in rock and its system response curve computed by the analytical program GDLAD\_Foundation*. Engineer Research and Development Center Technical Report ERDC TR-12-4. Pittsburgh, USA: United States Army Corps of Engineers.

Ellingwood, B., and Tekie, P. B. (2001). "Fragility analysis of concrete gravity dams." *Journal of Infrastructure Systems*, 7(2), 41-48.

Escuder-Bueno, I., Altarejos-Garcia, L., and Serrano-Lombillo, A. (2011). "Theme C - Estimation of the probability of failure of a gravity dam for the sliding failure mode." Paper presented at the XI ICOLD International Benchmark Workshop on Numerical Analysis of Dams, Valencia, Spain.

Escuder-Bueno, I., Mazzà, G., Morales-Torres, A., and Castillo-Rodriguez, J. T. (2016). "Computational aspects of dam risk analysis: findings and challenges." *Engineering*, 2(3), 319-324.

FERC. (2002). *Engineering guidelines for the evaluation of hydropower projects*. Washington DC, USA: Federal Energy Regulatory Commission.

FERC. (2014). *Risk-Informed Decision Making*. Washington DC, USA: FERC.

Fishman, Y.A. (2009). "Stability of concrete retaining structures and their interface with rock foundations." *International Journal of Rock Mechanics and Mining Sciences*, 46, 957-966.

Hartford, D. N. D., and Baecher, G. B. (2004). *Risk and uncertainty in dam safety*. London, UK: Thomas Telford.

Hartford, D. N. D., Baecher, G. B., Zielinski, P. A., Patev, R. C., Romanas, A., and Rytters, K. (2016). *Operational safety of dams and reservoirs - Understanding the reliability of flow-control systems*. London, UK: ICE Publishing.

Holický, M. (2009). *Reliability analysis for structural design*. Stellenbosch, South Africa: SUN MeDIA Publishing.

IS. (1984-1998). *Criteria for design of solid gravity dams*. New Delhi, India: Indian Standards.

Johansson, F., Westberg Wilde, M., Altarejos-García L. (2017). "Theme D, Risk Analysis—assessment of reliability for concrete dams." XIV ICOLD International Benchmark Workshop on Numerical Analysis of Dams, Stockholm, Sweden.

Jongejan, R. B., and Calle, E. O. F. (2013). "Calibrating semi-probabilistic safety assessments rules for flood defences. " *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*. doi:10.1080/17499518.2013.790731

Jongejan, R. B., and Maaskant, B. (2013). "The use of quantitative risk analysis for prioritizing flood risk management actions in the Netherlands." Paper presented at the 2013 CDA Annual Conference, Montreal, Canada.

Kalinina, A., Spada, M., Marelli, S., Burgherr, P., and Sudret, B. (2016). *Uncertainties in the risk assessment of hydropower dams - State-of-the-art and outlook*. Technical report. Zürich, Switzerland: ETH.

Kovarik, J.-B. (2000). "What is a safety factor in civil engineering? (in French: "Qu'est-ce qu'un coefficient de sécurité en génie civil ?")." *Revue Française de Génie Civil*, 4(6), 607-651.

Kreuzer, H. (2000). "Risk analysis for existing dams: merits and limits of credibility." *Hydropower & Dams*, 7(1), 49-53.

Kreuzer, H. (2003). "Uncertainty in the assessment of failure probabilities." *Hydropower & Dams*, 10(6), 98-101.

Kreuzer, H., and Léger, P. (2013). "The Adjustable Factor of Safety: A reliability-based approach to assess the factor of safety for concrete dams." *Hydropower & Dams*, 20(1), 67-90.

Krounis, A., and Johansson, F. (2012). "The influence of correlation between cohesion and friction angle on the probability of failure for sliding of concrete dams." In Escuder-Bueno. et al. (Ed.), *Risk Analysis, Dam Safety, Dam Security and Critical Infrastructure Management*. London: Taylor & Francis Group.

Krounis, A., Johansson, F., Spross, J., and Larsson, S. (2016). "Influence of cohesive strength in probabilistic sliding stability reassessment of concrete dams." *Journal of Geotechnical and Geoenvironmental Engineering*. doi:10.1061/(ASCE)GT.1943-5606.0001583

Lombardi, G. (1988). "Logarithmic double-bounded distribution (in French: "Distribution à double borne logarithmique")." Paper presented in the 16<sup>th</sup> ICOLD Congress, San Francisco, Q.63, R.17, pp.1337-1348, USA.

Lombardi, G. (1993). "Concrete dams and their foundation - Evaluation for static loading." Paper presented at the International Workshop on Dam Safety Evaluation, Grindelwald, Switzerland. Vol.4, 77-90.

Lombardi, G. (2006). "Tendencies, probabilities and risk analysis for dams." *Dam Engineering*, 17(1), 5-29.



Luhmann, N. (2005). *Risk - A sociological theory*. London, UK: Aldine Transaction Publisher.

McCann, M.W., Franzini, J.B., Kavazanjian, E., Shah, H.C. 1985. *Preliminary safety evaluation of existing dams*, Vol. I, Report No. 69, Department of Civil Engineering, Stanford University.

Morin, S. (2016). R-AFS Version 1.6. Ecole Polytechnique de Montréal.

Peyras, L., Carjaval, C., Felix, H., Bacconnet, C., Royet, P., and Boissier, D. (2012). "Probability-based assessment of dam safety using combined risk analysis and reliability methods – Application to hazards studies." *European Journal of Environmental and Civil Engineering*, 16(7), 795-817.

Peyras, L., Royet, P., Deroo, L., Albert, R., Becue, J.-P., Aigouy, S., Bourdarot, E, Loudiere, D., and Kovarik, J.-B. (2008). "French recommendations for limit-state analytical review of gravity dam stability." *European Journal of Environmental and Civil Engineering*, 12(9-10), 1137-1164.

Porter, K. (2017). *A beginner's guide to fragility, vulnerability, and risk*. University of Colorado Boulder.

Riley, K., Webley, P., and Thomson, M. (2017). *Natural hazard uncertainty assessment: Modeling and decision support* (Vol. 223). Hoboken, USA: John Wiley & Sons.

Rocha, M. (1974). *Present possibilities of studying foundations of concrete dams*. Paper presented at the Third Congress of the International Society of Rock Mechanics, Denver, USA.

Ruggeri, G. (2004). *Sliding safety of existing gravity dams - Final report*: ICOLD European Club.

SPANCOLD. (2003). *Dam safety technical guidelines N°2: Criteria for dams and associated works projects (in Spanish: "Guía Técnicas de Seguridad de Presas N° 2: Criterios para proyectos de presas y sus obras anejas")*. Madrid, Spain: Spanish Committee on Large Dams.

SPANCOLD. (2013). *Risk analysis applied to management of dam safety*. Madrid, Spain: SPANCOLD.

Spross, J., Johansson, F., and Larsson, S. (2013). "On the use of pore pressure measurements in safety reassessments of concrete dams founded on rock." *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*, 8(2), 117-128.



Tekie, P. B. (2002). *Fragility Analysis of Concrete Gravity Dams*. USACE ERDC Technical Report TR-02-6. Washington DC, USA: USACE.

The MathWorks, I. (2016). MATLAB R2016a.

USACE. (2005). *Stability analysis of concrete structures*. Washington DC, USA: USACE.

USACE. (1995). *Gravity dam design*. Washington DC, USA: USACE.

USBR. (1976). *Design of gravity dams*. Denver, USA: United States Bureau of Reclamation.

Vergouwe, R. (2016). *The national flood risk analysis for the Netherlands. Final report*. The Netherlands: Rijkswaterstaat VNK Project Office.

Westberg Wilde, M., and Johansson, F. (2013). "System reliability of concrete dams with respect to foundation stability: Application to a spillway." *Journal of Geotechnical and Geoenvironmental Engineering*, 139(2), 308-319.

Westberg Wilde, M., and Johansson, F. (2016). *Probabilistic model code for concrete dams*. Report 2016:292. Stockholm, Sweden: Energiforsk.

Zhang, L., Peng, M., Chang, D., and Xu, Y. (2016). *Dam failure mechanisms and risk assessment*. Singapore: John Wiley & Sons.

**Appendix 1 – ICOLD Benchmark material data**

The fifteen couples of friction angle  $\phi$  (°) and cohesion C (kPa) specified as input "material test" data in the 11th ICOLD Numerical Benchmark (Escuder-Bueno, Altarejos-Garcia and Serrano-Lombillo 2011) are:  $(\phi, C) = \{(45, 500); (37, 300); (46, 300); (45, 700); (49, 800); (53, 200); (54, 600); (45, 0); (49, 100); (60, 200); (63, 200); (62, 400); (60, 700); (56, 100); (62, 400)\}$ .

## Abstract

Structural sliding stability of gravity dams is most often quantified using a binary safe/unsafe criterion such that the shear resistance has to be larger than the driving shear load. Large deterministic factors of safety,  $FS_{det}$  (e.g. 3 in normal condition), are used in existing guidelines to guard against material and loads uncertainties. Some guidelines allow an arbitrary reduction in  $FS_{det}$  (e.g. 2) when the knowledge in strength parameters increases from material test data. Yet, those reduced  $FS_{det}$  are not based on a rational consideration of uncertainties. Propagation of uncertainties could be done using comprehensive probabilistic analyses, such as Monte-Carlo simulations (MC). However, MC are complex and challenging for practical use. There is thus a need to develop simplified reliability based safety assessment procedures that could rationalise the adjustment of  $FS_{det}$  from existing dam safety guidelines. This paper presents a progressive analysis methodology using four existing safety evaluation formats of increasing complexity: (i) deterministic, (ii) semi-probabilistic (partial coefficient), (iii) reliability based *Adjustable Factor of Safety (AFS)*, and (iv) probabilistic (MC). Comprehensive comparisons are made for the sliding safety evaluation of a 80 m gravity dam. Results are presented in terms of sliding factors of safety, allowable water levels, and demand/capacity (load and resistance) ratios. It is shown that the reliability based AFS formulation, using direct integration, is simple and practical to use in complement to existing dam safety guidelines before undertaking MC simulations. AFS yielded results with a maximum difference of approximately 10% as compared to rigorous MC probabilistic analyses.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

# 1. Introduction

Dams are major infrastructures, for which failure is an extremely rare event but with very serious consequences. Gravity dams are particularly sensitive to overtopping, due to the large hydrostatic thrust and uplift pressures that reduce the shear strength capacity that could be mobilised by frictional resistance and cohesion along lift joints or the concrete-rock interface. Dams have a useful service life extending for decades, such that aging of materials and the magnitude of anticipated floods evolve with advances in predictive methodologies and changes in the environment. The structural stability of major dams needs to be re-evaluated every 5-10 years according to Hazard Classification Systems (HCS), most often within the legal framework of a governmental regulatory agency.

Structural stability against sliding should satisfy a binary safe/unsafe limit-state stating that the shear resistance,  $R$ , has to be strictly larger than or equal to the driving shear load,  $L$ . To guard against uncertainties in  $R$  and  $L$ , large deterministic factors of safety ( $FS_{det}$ ) are used. These large  $FS_{det}$  may be reduced when new knowledge about the material shear strength parameters is acquired to better quantify the friction coefficient and cohesion. For instance, in CDA (2007),  $FS_{det} = 3$  if no material test is available, and  $FS_{det} = 2$  if tests are done. A better knowledge of strength parameters thus authorises a reduced safety margin. However, the specified  $FS_{det}$  numerical values ~~come~~ **are rounded numbers from** experience and not from a rational approach to quantify reduction in strength parameters uncertainties. There is thus a need to develop, validate and verify simplified reliability based safety assessment procedures that could rationalise the  $FS_{det}$  adjustment ~~from existing dam safety guidelines, used routinely by practicing engineers~~ **by referring to data bases developed from evaluating  $L$  and  $R$  uncertainties readily available from countless test series and load**

statistics (Kreuzer and Léger 2013). Simplified methods should be robust, computationally efficient, with a limited number of random variables, and easily interpretable., and should be integrated as an extension of existing guidelines. They then can replace the deterministic L and R parameters. Moreover, reliability based safety assessment should will also answer a societal aspect in form of relating the required safety margin to a HCS used by the dam safety regulations of the particular country, need of transparency, and be communicated to decision makers and stakeholders with clarity. Of course, comprehensive reliability based probabilistic analyses could be undertaken to propagate uncertainties in structural stability analyses. However, comprehensive probabilistic analyses (e.g. Monte Carlo (MC) simulations) require extensive time, sophisticated tools, expertise and resources that are most often not available. To adjust the required safety margin as a function of a reduction in shear strength uncertainties, this paper presents a progressive analysis methodology of increasing complexity and accuracy. It consists in applying successively (i) deterministic analyses, (ii) simplified reliability based *Adjustable Factor of Safety (AFS)* analyses, and (iii) full probabilistic analyses (crude MC). The main objective of the paper is to establish the range of AFS modelling parameters for which coherent results could obtained with MC simulations that are used as reference values.

This paper is organised as follows. After the review of literature in section 2, section 3 describes four different safety formats: (i) deterministic, (ii) semi-probabilistic (partial coefficient), (iii) reliability based AFS, and (iv) probabilistic (MC). Comprehensive comparisons of the four safety evaluation formats are done by comparing sliding stability indicators of a 80 m-high gravity dam, studied in a previous ICOLD numerical Benchmark seeking to quantify the sliding probability of failure,  $p_f$ , as a function of the upstream

reservoir water elevation,  $H_w$  (Escuder-Bueno ~~et al.~~, Altarejos Garcia and Serrano-Lombillo 2011). It is shown that coherent results, ~~as compared to MC, are~~ could be obtained while using the AFS ~~computation method when the required safety margin is being compared to the ratio of resistance and load mean values as compared to MC.~~ The AFS method is thus shown ~~as a simple and practical~~ preliminary substitute to full probabilistic MC analysis that may therefore be avoided within the scope of the gravity dam stability problem studied herein. ~~Two additional AFS safety margin formulations have also been investigated to demonstrated the AFS range of applicability as compared to MC (i) when all uncertainties have been factored in AFS parameters such that  $AFS \geq 1$ , and (ii) when an additional safety margin is deemed necessary to account for ignorance, or lack of information in spite of having considered uncertainties with all AFS factors (Kreuzer and Leger 2013).~~ ~~in a much simpler and practical way.~~

**2. Stability assessment of gravity dams considering uncertainty analysis**

One can solve the gravity dam stability problem as a deterministic one where there is no uncertainty. At the other end of the spectrum, total ignorance of phenomena that may affect stability, and its outcome, cannot be quantified because classification and identification of what is unknown is not possible (Riley, Webley and Thomson 2017; D. Rumsfeld famous deep "unknown-unknown" uncertainty; Baecher 2016). We will therefore focus our analysis on epistemic and aleatory uncertainties in input data (friction coefficient and cohesion) that admit statistical descriptions from a frequentist point of view.

**Deterministic analysis** is traditionally used to assess the stability of dams (ANCOLD 2013; CDA 2007; FERC 2002; Ruggeri 2004; USBR 1976; USACE 1995, 2005). Deterministic

1  
2  
3 methods do not allow accounting explicitly for uncertainties in strength capacity and load  
4 effects (stresses). Moreover, deterministic FSs are round numbers without rational safety-  
5 relevant significance, apart from grading them to the frequency of load combination (usual,  
6 unusual, extreme). There is thus a huge interest in the profession to move towards more  
7 refined probabilistic methods to consider uncertainties.

8  
9  
10 *Probabilistic analysis* allows ~~quantifying engineering judgement considering nature's~~  
11 randomness, and human incomplete knowledge within the probabilistic safety evaluation.  
12 Mathematical constructs are used normally presented by probability density functions and  
13 engineering judgment. Then, comparisons between several failure scenarios ~~options~~ are  
14 possible while assessing probability of failure,  $p_f$ , and related risk according to the  
15 consequence model. Probabilistic methods are thus very useful tool to decision-making  
16 (Bury and Kreuzer 1985; FERC 2014). Probabilistic risk analysis, and associated risk  
17 management, are used for other civil structures and are now in active development in dam  
18 engineering (Baecher 2016; FERC 2014; Hartford and Baecher 2004; Hartford et al. 2016;  
19 Kalinina et al. 2016; Peyras et al. 2010; Peyras et al. 2012; SPANCOLD 2013; Westberg  
20 Wilde and Johansson 2016; Zhang et al. 2016). As dam engineering is moving towards  
21 models accounting for uncertainties, ICOLD organized an International Benchmark  
22 Workshop on Numerical Analysis of Dams in 2011 to examine probabilistic analysis  
23 (Escuder-Bueno et al., ~~Altarejos-Garcia and Serrano-Lombillo~~ 2011). A new ICOLD  
24 Benchmark on Risk Assessment ~~will take~~ place in 2017 (Johansson et al. 2017). Risk  
25 assessment uses probabilistic methods, and consists (i) to combine failure modes to  
26 determine a failure scenario ~~by using event or failure trees; a tree of events is often used,~~  
27 (ii) to model ~~each~~ failure modes, (iii) to ~~compute~~ assess the failure probability for each  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

failure mode, (iv) to deduce the total dam failure probabilities for the whole scenario. The concept of "As Low As Reasonably Possible (ALARP)" is then used in several dam safety guidelines to answer the difficult question "How safe is safe enough?" (Bowles 2007). ALARP is used to accept or reject the resulting failure probability and related consequences. Recognising that absolute safety cannot be achieved, the mathematical concept of risk is used to specify reasonable efforts to avert losses considering what can be achieved with the available resources. Reasoning in terms of probability of failure and acceptable risks is a key societal construct, subjected to time evolution. While accepting the ALARP principle, it is then possible to make the transition between the deterministic world, where achieving the required  $FS_{det}$  is believed to provide absolute safety, and the probabilistic world where uncertainties are explicitly recognised (Luhmann 2005).

A probabilistic analysis could account for uncertainties in cohesion, friction, drain efficiency, and several other parameters as shown in Altarejos-Garcia et al. (2015, 2012). Probabilistic analysis also allows reliability assessment of dam-foundation-reservoir systems (Westberg Wilde and Johansson 2013). In probabilistic reliability-based safety assessment, fragility analysis, first used in seismic evaluation of nuclear power plants, is a key step (Porter 2017). Fragility analysis is the computation of the probability to reach an undesirable limit-state for a known loading intensity. Fragility curves, expressed as function of reservoir elevation,  $H_w$ , provide quantitative cumulative distribution functions for the dam to resist sliding. Fragility functions are used in damage analysis that is combined with loss analysis to quantify risk (Porter 2017). Fragility curves provides a rational tool that could be used to compare several remedial options if a need for strengthening is identified (Ebeling et al. 2012; Ellingwood and Tekie 2001; Tekie 2002).



However, probabilistic assessments require many parameters to describe uncertainties, such as random variables, Probability Density Functions (PDF), PDF bounds, coefficients of variation, which may affect substantially the analysis results as shown by the wide dispersion in fragility curves computed from the participants in the ICOLD Benchmark (Escuder-Bueno et al. 2016). Then, the decision to take remedial action, if necessary, depends on a complex and possibly not unique assessment: one may wonder about limits of reliability methods, which are finally not the unerring reference (Kreuzer 2000, 2003).

***Semi-probabilistic (partial coefficient) analysis*** is a first simplified approach that allows considering uncertainties according to each load and resistance parameter (ANCOLD 1991; CFBR 2013, 2015; IS 1984-1998; Peyras et al. 2008; Rocha 1974; SPANCOLD 2003). Partial safety coefficients are ideally calibrated according to probabilistic analyses. However, each dam is a unique hydro-geomechanical system. Calibration may not be based on consistent sampling, but adapted to correspond to existing structures designed with deterministic methods (Jongejan and Calle 2013; Kovarik 2000). In the Netherlands, the National Flood Risk Analysis project developed recommendations evolving from deterministic to semi-probabilistic analysis to assess stability of hydraulic structures (levees), using probabilistic analysis to calibrate coefficients according to target failure probability,  $p_f^*$  (Jongejan and Maaskant 2013; Vergouwe 2016).

***Adjustable Factor of Safety (AFS)*** analysis is another simplified and practical way to perform probabilistically (reliability) based safety assessment. AFS considers only two basic random variables, the resistance  $\mathbf{R}$  and the load,  $\mathbf{L}$ . AFS is seeking a binary outcome such that  $AFS \geq FS_{req}$ , where  $FS_{req}$  is depending on a user defined target  $p_f^*$  or a target



reliability index,  $\beta^*$ . As described in more details in section 3, AFS connects R and L within a probabilistic framework using their PDF along with six uncertainty factors calibrated on empirical evidences, including coefficients of variations as well as upper (for L) or lower (for R) PDF bounds (Kreuzer and Léger 2013). ~~More comprehensive probabilistic analyses may attempt a solution requiring much more extensive numerical data processing. However, no matter how mathematically elaborate is a probabilistic analysis, it cannot avoid the key difficulty of acquiring data to characterise each random variable from reliable empirical evidences.~~

A progressive approach, with increasing level of complexity to assess the sliding stability of gravity dams is therefore proposed as follows: (i) deterministic analysis is done first, (ii) then semi-probabilistic method can optionally be used to distinguish uncertainties about the friction coefficient and cohesion. (iii) The AFS method is next performed to rationally adjust the computed  $FS_{det}$  and compared it to  $FS_{req}$  considering a probabilistic description of R uncertainties and a selected target  $p_f^*$  or  $\beta^*$ . Finally, (iv) full probabilistic analysis may be undertaken if deemed necessary.

**3. Quantitative Specification for requiredments in safety margins in investigated safety evaluation formats**

**3.1 Deterministic**

Deterministic analysis is traditionally used to design and assess dam stability. It consists in defining a factor of safety (FS) between the dam’s resistance R and the loading L from  $FS = R/L$ , and to compare it to required values according to applicable guidelines. The gravity method and Mohr-Coulomb criterion are most often employed to define the shear

strength resistance to compute sliding FS. Typically, three values for resistance are considered in parametric study: best estimate, lower bound, and upper bound. Different load combinations are considered, only those associated with water levels are studied herein: usual, unusual, and extreme (flood). Moreover, required FS relate to dam-foundation interface and lift joints. ~~These coefficients come from experience and have no sound mathematical justification.~~

Some guidelines require FS without any consideration to the level of knowledge about strength parameters (Table 1). Some other guidelines recommend FS considering the level of knowledge in strength parameters. The required FS are larger if no material tests have been realised (Table 2).

Table 1. Required deterministic factors of safety without any explicit consideration of uncertainties.

Load combination	Required factor of safety		
	UBSR (1976)	USACE (1995)	FERC (2002) <sup>(a)(b)</sup>
Usual	3.0	2.0	3.0
Unusual	2.0	1.7	2.0
Extreme	1.0	1.3	-

<sup>(a)</sup> Dams are categorised according to the consequences of a failure: the coefficients are for a dam with moderate to high risks.

<sup>(b)</sup> Other FS are required for friction only (cohesion is null).

Table 2. Required deterministic factors of safety depending on the level of knowledge of strength parameters.

Load combination	Required factor of safety					
	CDA (2007) <sup>(a)</sup>		ANCOLD (2013) <sup>(a)</sup>		USACE (2005) <sup>(b)</sup>	
Knowledge?	No tests	With tests	Not well-defined <sup>(c)</sup>	Well-defined <sup>(c)</sup>	Well-defined <sup>(d)</sup>	Ordinary
Usual	3.0	2.0	3.0	2.0	2.0	1.7
Unusual	2.0	1.5	2.0	1.5	1.5	1.3
Extreme	1.3	1.1	1.5	1.3	1.1	1.1

<sup>(a)</sup> Other FS are required for friction only (CDA 2007) or residual values for  $C$ ,  $\tan\phi$  (ANCOLD 2013).

<sup>(b)</sup> Dams are categorised according to the consequences of a failure: the FS are for a dam with moderate to high risks.

<sup>(c)</sup> According to ANCOLD (2013), "well-defined" means that "a sufficient number of tests have been done to specify the strength parameters with reasonable certainty (e.g. assumed strength is exceeded by 80% of the test results from a test regime involving a significant number of tests)".

<sup>(d)</sup> According to USACE (2005), site information is "well-defined" when records are available, dam is monitored, uplift are known, and "foundation strengths can be established with a high level of confidence".

3.2 Semi-probabilistic (partial coefficients)

Rocha (1974) suggested to introduce partial safety coefficients for friction and cohesion instead of a single FS. This approach is to account for different levels of uncertainties in these two shear strength mechanisms. Divisor coefficients of 1.5 to 2, and 3 to 5, could be applied respectively to the friction coefficient,  $\tan\phi$ , and the cohesion, C. It is thus recognised that uncertainties in cohesion are more important than in friction, whereas there is no mathematical justification for the recommended values. Thereafter, countries like India (IS 1984-1998) and Spain (SPANCOLD 2003) chose to use the concept of partial strength reduction coefficients (Table 3).

Semi-probabilistic assessment consists in using some partial safety coefficients for both loads and strengths, increasing loads and reducing strengths depending on the target reliability of the structural component. These coefficients are ideally calibrated from probabilistic methods, and adapted to existing structures designed with deterministic analysis (Jongejan and Calle 2013; Kovarik 2000).

Table 3. Semi-probabilistic partial safety coefficients

Load combination	Partial safety coefficients							
	IS (1984-1998)		SPANCOLD (2003) <sup>(b)</sup>		CFBR (2013)		ANCOLD (1991) <sup>(c)</sup>	
	$\gamma_C$ <sup>(a)</sup>	$\gamma_{\tan\phi}$	$\gamma_C$	$\gamma_{\tan\phi}$	$\gamma_C$	$\gamma_{\tan\phi}$	Strength	Load <sup>(d)</sup>
Usual	3.6	1.5	5.0	1.5	3.0	1.5	0.3	
Unusual	3.6	1.5	4.0	1.2	2.0	1.2	0.4	

Extreme – flood	1.2	1.0	3.0	> 1.0	1.0	1.0	0.8
-----------------	-----	-----	-----	-------	-----	-----	-----

(a)  $C$  is the cohesion,  $\tan\phi$  is the friction coefficient;  $\gamma_C$  and  $\gamma_{\tan\phi}$  are associated partial safety coefficients such that semi-probabilistic sliding stability limit-state criterion is:  $\frac{A_c \cdot C / \gamma_C + V \cdot \tan\phi / \gamma_{\tan\phi}}{L} > 1.0$  where  $V$  is the sum of vertical forces,  $A_c$  the compressed sliding area,  $L$  the hydrostatic thrust (IS 1984-1998; SPANCOLD 2003; CFBR 2013).

(b) Dams are categorised according to the consequences of failure: the coefficients are for a dam with moderate to high risks.

(c) Multiplier coefficients applied to strength and load parameters to compute  $R'$  and  $L'$  such that semi-probabilistic sliding stability limit-state criterion is:  $R' > L'$  (ANCOLD 1991).

(d) Coefficients for loads are 0.95 for water and well-known dead loads contributing to stability, 0.90 for not well-known concrete weight, 1.05 for water, uplift and dead loads contributing to instability, 1.50 for live and silt loads contributing to instability.

### 3.3 Probabilistic

**Deterministic** FS and partial safety coefficients do not inform about the safety margin including uncertainties about parameters employed in analysis. Probabilistic analysis allows to compute a failure probability,  $p_f$ , considering mathematically uncertainties. HCS have been developed to differentiate structures according to the consequences a failure. The ALARP concept has often been used to link loss of human lives (or persons in danger), more than material costs of consequences, to recommended acceptable failure probability (Figure 1).




Figure 1. Concept of "As Low As Reasonably Possible" adapted from (CDA 2007).

In probabilistic analysis, load (L) and resistance (R) parameters are statistically distributed according to PDF selected to be representative of tests and knowledge about these parameters. Failure develops when internal load demand exceeds the resistance capacity of the dam. Influences of different selections of PDF data in probabilistic analyses have been studied in Altarejos-Garcia et al. (2012); Carjaval et al. (2009a, 2009b, 2009c); Carjaval, Peyras, and Baconnet (2010); Krounis and Johansson (2012); Krounis et al. (2016); Lombardi (1988, 1993, 2006); Spross, Johansson and Larsson (2013). Probabilistic analysis, no matter how sophisticated, can still lead to very different solutions for a given problem because of the complex choices of random variables, characteristic values, PDF, bounds, which can largely influence final results. For example, Figure 2 illustrates the wide dispersion obtained from participants in an ICOLD Benchmark seeking to compute the fragility curve ( $F_{curve}$ ) for  $p_f$  as a function of  $H_w$  for a 80 m-high gravity dam given fifteen sets of "cohesion, friction angle" data pair representing material test data. The detailed description of the problem is given in section 4.1 of this paper. In Figure 2, we present results from all participants that used MC simulations, ( $F_{curves}$  1-7) as well as our own MC solutions ( $F_{curves}$  8-12). Using the same PDF data for  $C$  and  $\tan\phi$ , ICOLD  $F_{curve}$  2 is similar to  $F_{curve}$  8 computed herein for water levels ranging from 75 m to 80 m. Our MC probabilistic analysis procedure is thus validated for the selected PDF data.




Figure 2. Dispersion in fragility curves computed for the ICOLD Benchmark for a 80 m-high gravity dam (Fig. 5);  $\phi$  is the friction angle, C the cohesion, R the global resistance of the dam defined in Eq. 2; N = normal distribution, LN = lognormal distribution; selected bounds are indicated. Fcurves 1 to 7 are from participants in the ICOLD Benchmark, Fcurves 8 to 12 are our solutions to the Benchmark.

### 3.4 Reliability based **Adjustable safety Factors of Safety**: AFS

Kreuzer and Léger (2013) presented a simplified reliability based method to assess dam stability. It depends on two uncertain random variables, R and L. An *Adjustable Factor of Safety (AFS)* is defined by:


$$AFS = \frac{\mu_R \{1 - (k_R \cdot c_R + \alpha_R)\}}{\mu_L \{1 + (k_L \cdot c_L + \alpha_L)\}} = FS_{det} \cdot U_{RL} \quad (\text{Eq. 1})$$

$FS_{det}$  is the deterministic factor of safety,  $c_R$  and  $c_L$  are the coefficients of variation related to physical uncertainties, the natural intrinsic dispersion of values,  $k_R$  and  $k_L$  are related to

1  
2  
3 statistical uncertainties defined herein as the lack of knowledge, from the number and  
4 reliability of material test data and  $\alpha_R$  and  $\alpha_L$  are related to model or (epistemic)  
5 uncertainties (Figure 3). Comprehensive description and numerical values for these  
6 coefficients have been suggested in Kreuzer and Léger (2013) depending on the knowledge  
7 of the structure.  
8

9  
10 Considering only two random variables, R and L, the AFS aims to be compared to a  
11 Required Safety Factor,  $FS_{req}$ , depending on a target failure probability,  $p_f^*$ , or the  
12 corresponding reliability index  $\beta^*$ . For a safe structure, the stability criterion becomes  
13  $AFS \geq FS_{req}$ .  $FS_{req}$  is computed iteratively by direct integration to be the  $FS = \mu_R/\mu_L$  such  
14 that with the selected PDF data for R and L, the computed  $p_f$  would correspond to the target  
15 failure probability,  $p_f^*$ . PDF are bounded at distances from the mean corresponding to a  
16 number  $k_R$  or  $k_L$  of standard deviations, on the left for the resistance and on the right for  
17 the load. For unbounded PDF, tails of distributions are considered in the computation of  
18  $FS_{req}$  (it would correspond to  $k = \infty$ ), but a  $k$  value has to be defined for the computation of  
19 AFS.  $FS_{req}$  decreases when the uncertainties in L and R are reduced. The AFS is a simple  
20 approach to introduce uncertainties using PDF data of the basic random variables **L** and **R**  
21 directly into the safety evaluation process. It allows to study the effect of reducing the  
22 coefficient of variation of the resistance,  $c_R$ , using material tests, on a rational basis as  
23 opposed to existing deterministic dam safety guidelines using arbitrary reduced FS  
24 requirements. The AFS considers only  $p_f^*$ , that could be specified directly from a HCS,  
25 avoiding to rely on assessing speculative terms of risk which require a complementary loss  
26 model. A user friendly open source computer program, **R-AFS**, was developed to perform  
27 AFS and  $FS_{req}$  computations (Morin 2016). The R-AFS implementation is controlled by an  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

While discussing AFS with colleagues, we realized that the expression "*Adjustable*" is unfortunate because for some it conveys the impression of an *arbitrary* adjustment instead of a reliability based adjustment using sound principles. We are thus using below the expression Reliability Based Safety Factor (RBSF). RBSF is, we believe, more suitable to convey the essence of the proposed simplified method.



The advantages of the reliability-based AFS are (i) the rationality to account for uncertainties using selected PDF data and a target  $p_f^*$  (or  $\beta^*$ ) in similarity to probabilistic analysis, (ii) its simplicity and practical use, (iii) a clear interpretation in the form of a binary decision to accept/reject the computed FS.

**URL:** <http://mc.manuscriptcentral.com/ngrk>



satisfy  $(\mu_R/\mu_L) \geq FS_{req}(c_R, k_R, \alpha_R, p_f^*)$ . However, an additional safety margin might be provided for initial imperfection, ignorance or lack of information leading to the acceptance criterion  $AFS \geq FS_{req}(c_R, k_R, \alpha_R, p_f^*)$  (Kreuzer and Léger 2013). These three acceptance criteria (i)  $AFS \geq 1$ , (ii)  $(\mu_R/\mu_L) \geq FS_{req}$ , and (iii)  $AFS \geq FS_{req}$  are compared with MC analyses, used as the reference solution to evaluate the reliability-based AFS RBFS method.

3.5 Progressive approach to introduce uncertainties

The above safety evaluation formats, ranging from deterministic to comprehensive probabilistic analyses, show different ways to account for uncertainties, from various sources appearing at each level of the stability assessment of the dam: material testing, selection of strength and load parameters, structural model. A progressive approach may then be developed to best account for these uncertainties, from simple to more complex but more precise evaluation formats (Figure 4).




Figure 4. Progressive approach for dam safety assessment: parameters, sources of uncertainties and performance indicators.

## 4. Application of progressive safety assessment

### 4.1 Description of the gravity dam for applications

The dam for applications is a 80 m-high concrete gravity dam that might be subjected to overtopping. The dam geometry (Figure 5) is given in the 11th ICOLD Numerical Benchmark (Escuder-Bueno *et al.*, Altarejos-Garcia and Serrano-Lombillo 2011). A single and simple failure mode, corresponding to horizontal sliding along the dam-foundation interface, is to be investigated. In reality, the kinematic of a dam base sliding-turning failure mode might occur along inclined planes propagating in the foundation (Fishman 2009). However, our study is restricted to the ICOLD benchmark problem to allow comparisons with previously published results (Fig. 2). The resistance,  $R$ , is a function of two basic

random variables, (i) the friction coefficient,  $\tan\phi$ , and (ii) the cohesion,  $C$ . The dam weight,  $W$ , and the drain effectiveness,  $E$ , are considered as given constant parameters. The uplift pressure,  $U$ , is a function of the water level,  $H_w$ . In this application, there is no uncertainty for the load,  $L$ . The water level,  $H_w$ , is increased systematically to reach an unacceptable limit state. In the case of overtopping, the water weight on the crest is estimated as  $W_w$ . The gravitational acceleration, the dam-foundation interface tensile strength, the water and concrete densities used in computations are respectively,  $g = 9.81 \text{ m/s}^2$ ,  $f_t = 0$ ,  $\rho_w = 1000 \text{ kg/m}^3$ , and  $\rho_c = 2400 \text{ kg/m}^3$ . The classical gravity method is used in stability analyses, considering cracking at the dam-foundation interface. If the base crack extends beyond the drain, the full uplift pressure is considered in the crack.




Figure 5. Geometry, load, L, drainage, and resistance, R, (friction and cohesion) properties of the gravity dam analysed.

Fifteen couples of friction angle  $\phi$  ( $^{\circ}$ ) and cohesion  $C$  (kPa) are specified as input "material test" data in the 11th ICOLD Numerical Benchmark seeking to estimate the sliding probability of failure,  $p_f$ , of the dam (see Appendix 1). The statistics for  $C$  and the friction coefficient,  $\tan\phi$ , are summarised in Table 4. The coefficient of variation for cohesion,  $c_c$ , is 0.67, which is quite large. Distribution fitting has been realised with N-PDF and LN-PDF. The LN-PDF was found to suit the data best taking into account the skewness, whereas N-PDF is symmetrical.

Table 4. Material test data statistics for friction and cohesion at the dam-foundation interface.

Material test	Cohesion C (kPa)	Friction angle $\phi$ (°)	Friction coefficient $\tan\phi$
Mean $\mu$ – best estimate	367	52.4	1.36
Standard deviation $\sigma$	247	7.99	0.39
Coefficient of variation c	0.67	0.15	0.29
Minimum – lower bound	0	37	0.75
Maximum – upper bound	800	63	1.96
5% fractile – N	0	39.3	0.72
5% fractile – LN	112	40.3	0.82

4.2 Deterministic stability evaluation

Deterministic analyses are first realised with mean values selected as best estimates for cohesion, C, and friction coefficient,  $\tan\phi$ . Smallest and largest values are taken as lower and higher bounds. For the usual and unusual load combinations, the maximal allowable water level,  $H_w$ , is computed according to CDA (2007, Table 2), without and with material tests (Figure 6).




Figure 6. Maximum allowable water level according to deterministic CDA (2007) dam safety guidelines.

These results indicated the importance of having a good knowledge of shear strength parameters. For the usual load combination, the allowable water level increased by 10 m if material tests are realised. However, CDA (2007) does not provide clear guidance on the number of tests, the sampling location and the testing method to be used to obtain representative results with a quantified confidence level. ANCOLD (2013) suggests criteria for the "well-defined" material shear strength parameters (Table 2).

#### 4.3 Probabilistic safety evaluation using Monte-Carlo simulations

A probabilistic assessment requires to select a target  $p_f^*$ , random variables, their PDF, and their bounds if they are bounded. PDF are bounded at distances from the mean corresponding to a number  $m$  of standard deviations on the left and on the right. Unbounded PDF corresponds to  $m = \infty$ . Herein, the  $p_f^*$  is  $10^{-5}$ , consistent with the ALARP principles for a high-risk dam (CDA 2007). We work with two sets of random variables either  $(C, \tan\phi)$  or  $R$ . The resistance,  $R$ , is described as the sum a friction and a cohesion component:

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

$$R = V \cdot \tan\phi + A_c \cdot C \quad (\text{Eq. 2})$$

a mean value is computed for R and the standard deviation,  $\sigma_R$ , is estimated from:

$$\sigma_R = \sqrt{(V \cdot \sigma_{\tan\phi})^2 + (A_c \cdot \sigma_C)^2} \quad (\text{Eq. 3})$$

where V is the sum of vertical forces, and  $A_c$  the area in compression.

The related PDF are successively selected as N and LN in sensitivity analyses. Bounded and unbounded PDF are also studied. MC computations are realised with MATLAB® (The MathWorks 2016),  $n = 10^7$  samples are found adequate to obtain convergence for  $p_f$ . For instance, when  $p_f = 10^{-5}$ , the accuracy is  $p_f = 10^{-5} \pm 5 \cdot 10^{-7}$ .

**Unbounded PDF** are first studied. When the unbounded hypothesis is considered with N-PDF, negative values of C,  $\tan\phi$ , or R, are replaced by new draws in MC simulations. The results are presented in Figure 7. LN-PDF yielded failure probabilities smaller than N-PDF. The reduction from two random variables, (C,  $\tan\phi$ ), to one random variable, R, gave similar  $H_w$  results.




Figure 7. Fragility curves comparing **unbounded** N-PDF and LN-PDF, variables (C,  $\tan\phi$ ) or R, computed with MC; and  $H_w$  according to probabilistic analysis for a target failure probability  $p_f^* = 10^{-5}$ .

The effect of **bounded PDF** is investigated by selecting values between the 5% fractile for strength parameters on the left of the distribution:  $m_l$  standard deviations, and the 95% fractile on the right:  $m_r$  standard deviations (Figure 8). For variables C,  $\tan\phi$ , R,  $m_l$  are respectively equal to 1.03, 1.38, 1.39 and  $m_r$  respectively equal to 1.88, 1.84, 1.83.






Figure 8. Fragility curves comparing **bounded** N-PDF and LN-PDF at the 5% and 95% fractile values, variables (C,  $\tan\phi$ ) or R, computed with MC; and maximum allowable water level according to probabilistic analysis for a  $p_i^* = 10^{-5}$ .

Results were similar using N-PDF or LN-PDF, but more sensitive to the selection of random variables. Using a single random variable, R, instead of two (C,  $\tan\phi$ ), yielded higher  $H_w$ .

4.4 Semi-probabilistic (partial coefficient) stability evaluation

For the semi-probabilistic analysis, CFBR (2013) suggests as characteristic values, a "wise estimation of the mean", and the 5% fractile if statistical methods are used. Herein, two pairs of (C,  $\tan\phi$ ) are used (i) mean values as best estimates (367, 1.36), and (ii) 5% fractile obtained from the 15 material test data assuming a N-PDF (0, 0.72, Table 4) considered in typical user of CFBR. The partial strength safety coefficients are applied for the usual, unusual, and extreme load combinations (Table 3).

With the extreme combination, the computed  $H_w$  was 106 m using the mean values for ( $C$ ,  $\tan\phi$ ), but as complete base cracking occurred at **104 m** we used this last value as the maximum  $H_w$ . Allowable  $H_w$  according to each load combination are presented in Figure 9.




Figure 9. Maximum allowable water level according to semi-probabilistic CFBR (2013) dam safety guidelines.

These results showed a very significant sensitivity of the semi-probabilistic method to the selected characteristic values.

#### 4.5 Reliability-based **Adjustable** Safety Factors – AFS

The selected  $p_r^*$  is  $10^{-5}$  as recommended for a high-risk dam with good quality assurance and management (Kreuzer and Léger 2013). The AFS method is employed without uncertainties in load  $L$ ,  $c_L = 0$ , also, coefficients reporting model uncertainties  $\alpha_R$  and  $\alpha_L$ .

are null. The shear strength random variable in the AFS method is  $R$ . The related PDF is LN as recommended in Kreuzer and Léger (2013).

**Unbounded PDF** are first studied. Tails of distributions are considered while computing  $FS_{req}$  but a value for  $k_R$  has to be defined for the evaluation of AFS. Values selected for  $k_R$  in the AFS computation (Eq. 1) are (i)  $k_R = 1.39$ , corresponding to the 5% fractile for  $R$  for LN-PDF (Holický 2009), (ii)  $k_R = 2$ , (iii)  $k_R = 3$ .  $FS_{req}$  is computed with unbounded PDF. Computed AFS and  $FS_{req}$  are presented in Figure 10. For  $k_R = 3$ , allowable water level was less than 40 m.




Figure 10. **AFS** method: deterministic  $FS_{det}$ ; required  $FS_{req}$  for  $p_r^* = 10^{-5}$  and **unbounded** LN-PDF for  $R$ ; and AFS for (i)  $k_R = 1.39$ , (ii)  $k_R = 2$ , (iii)  $k_R = 3$ .

For **bounded PDF** the effect of bounds is investigated by selecting (i)  $k_R = 1.39$  (corresponding to the 5% fractile for  $R$  for our LN-PDF (Holický 2009), (ii)  $k_R = 2$ , and (iii)  $k_R = 3$  for the computation of AFS as well as  $FS_{req}$ . The computed AFS and  $FS_{req}$  are presented in Figure 11. For  $k_R = 3$ ,  $H_w$  was again less than 40 m.




Figure 11. **RB-AFS** method: deterministic safety factor  $FS_{det}$ ; required safety factor  $FS_{req}$  for  $p_f^* = 10^{-5}$  and **bounded** LN-PDF for R; AFS and  $FS_{req}$  for (i)  $k_R = 1.39$ , (ii)  $k_R = 2$ , (iii)  $k_R = 3$ .

## 5. Discussion

### 5.1 Results from different safety evaluation formats

The 80 m dam was analysed according to four safety evaluation formats applying the proposed progressive safety assessment methodology. The key results are presented (i) in Figure 6 for deterministic analyses, (ii) in Figure 9 for semi-probabilistic analyses, (iii) in Figures 10-11 for **RB-AFS**, and (iv) in Figures 7-8 for probabilistic **MC** analyses. Comparative  $H_w$  results are presented in Figure 12. Table 5 presents the computed FS for each safety format that are compared to the required FS to declare a safe dam. The reference value to make comparisons and orient the discussion is  $H_w = 90$  m. This allowable  $H_w$  is computed from MC simulations, using  $C$  and  $\tan\phi$  as random variables, with LN-bounded

PDF ( $m_1 = 1.03$  for  $C$  and  $1.38$  for  $\tan\phi$ , corresponding to the 5% fractile). It is a reasonable and defensible probabilistic model having considered strength uncertainty in a rational way with two random variables, as well as existing dam safety guidelines to select PDF bounds. Obviously, other reference value for  $H_w$  could be selected. However, we present coherent hypotheses moving from one level of complexity to the next such that meaningful comparisons and discussion could be established.

The *deterministic* format criteria (Table 2, CDA 2007) are unable to consider the large coefficient of variation in shear strength parameters,  $H_w$  being **102 m** for extreme conditions (flood) if material tests had been realised. A parametric analysis showed that lower bound of shear strength data would authorise  $H_w$  equal to **82 m**.

*Probabilistic* sensitivity analyses were applied with random variables ( $C$ ,  $\tan\phi$ ) or  $R$ , LN-PDF, and unbounded or bounded distributions, with  $p_r^* = 10^{-5}$ . For the unbounded case,  $H_w$  was **76 m** with variables ( $C$ ,  $\tan\phi$ ) and **75 m** with variable  $R$ , leading to similar results. With bounds corresponding to the 5% fractiles for strength parameters,  $H_w$  was **90 m** (the reference value) for variables ( $C$ ,  $\tan\phi$ ) and **94 m** for  $R$ . Probabilistic analysis (MC) may be considered as the most rigorous approach but is shown to be sensitive to the selection of random variables and PDF bounds.

In *semi-probabilistic analysis*, two pairs of values for ( $C$ ,  $\tan\phi$ ) were used. For the extreme combination, using the mean,  $H_w$  was **104 m**. Using the 5% fractile,  $H_w$  was **83 m**. This 83 m value was the same as using bounded N-PDF with variables ( $C$ ,  $\tan\phi$ ) in probabilistic analysis (Figure 8), meaning that calibration of partial coefficients in semi-probabilistic analysis appears to be consistent with results of N-PDF bounded probabilistic analysis.

The *reliability-based adjustable safety factors (AFS)* with criterion " $AFS \geq FS_{req}$ " yielded very low  $H_w$  for unbounded LN-PDF. For unbounded PDF,  $H_w$  values were very sensitive to the coefficient  $k_R$ . It is deemed inadequate in our application.

The criterion " $AFS \geq 1$ " gave the same  $H_w$  for unbounded and bounded LN-PDF because this criterion is not related to the computation of  $FS_{req}$ , using PDF data. For  $k_R = 1.39$  and  $k_R = 2$ ,  $H_w$  obtained with the criterion " $AFS \geq 1$ " are the same as those obtained with criterion " $(\mu_R/\mu_L) \geq FS_{req}$ ". The criterion " $(\mu_R/\mu_L) \geq FS_{req}$ " gave the same  $H_w$  for unbounded PDF even for  $k_R = 3$ . This means that bounding PDF with large  $k_R$  is equivalent in ~~RBSF~~ **AFS** to consider the whole content of the distribution.

## 5.2 Comparisons of different safety evaluation formats

For the same 80 m gravity dam stability problem, with known 15 pairs  $(C, \tan\phi)$  and considering (i) no uncertainty, (ii) uncertainties believed to be known with certainty either in RBSF or probabilistic analysis or, (iii) uncertainties with an added safety margin, may decrease the allowable  $H_w$  from 104 m to 60 m (Figure 12). Table 5 presents FS computed by each safety evaluation format and the associated safety criterion for two water levels: 80 m and 90 m. Demand/capacity ratios  $(D/C)$  have been computed in each case as  $(H_w^2/90^2)$  because the applied hydrostatic thrust,  $L$ , could be estimated as  $L = (\rho_w g H_w^2)/2$ .  $D/C$  ratios are presented in enclosed boxes in Figure 12, and for varying values of PDF bounds,  $m_l$  (MC) and  $k_R$  (~~RBSF~~ **AFS**), in Figure 13.




Figure 12. Maximum allowable water level for different safety formats: (i) deterministic, (ii) semi-probabilistic, (iii) AFS criterion " $AFS \geq FS_{req}$ ", (iv) RBSF AFS criterion " $(\mu_R/\mu_L) \geq FS_{req}$ ", (v) probabilistic MC simulations with random variables (C, tan $\phi$ ), (vi) probabilistic MC simulations with random variable R. LN-PDF is used for RBSF AFS and probabilistic methods. In boxes are Demand/Capacity ratios.

Table 5. Sliding FS from safety formats: (i) deterministic (CDA 2007), (ii) semi-probabilistic (CFBR 2013), (iii) three criteria of **RBSF AFS** method, (iv) probabilistic (**MC simulations**).

	80 m - unusual		90 m - extreme	
<b>Deterministic</b>	FS <sub>det</sub>	FS <sub>det</sub> <sup>req</sup>	FS <sub>det</sub>	FS <sub>det</sub> <sup>req</sup>
FS <sub>det</sub> ≥ FS <sub>det</sub> <sup>req</sup>	2.84	≥ 1.5	1.86	≥ 1.1
<b>Semi-prob.</b>	FS' <sub>unus</sub>	FS' <sub>req</sub>	FS' <sub>extr</sub>	FS' <sub>req</sub>
FS' ≥ FS' <sub>req</sub>	2.14	≥ 1.0	1.86	≥ 1.0
<b>ASF</b> <sup>(a)</sup>	AFS	AFS <sup>req</sup>	AFS	AFS <sup>req</sup>
(i) AFS ≥ 1	1.77	≥ 1.0	1.17	≥ 1.0
(ii)	μ <sub>R</sub> /μ <sub>L</sub>	FS <sub>req</sub>	μ <sub>R</sub> /μ <sub>L</sub>	FS <sub>req</sub>
(μ <sub>R</sub> /μ <sub>L</sub> ) ≥ FS <sub>req</sub>	2.84	≥ 1.61	1.86	≥ 1.58
(iii)	AFS	FS <sub>req</sub>	AFS	FS <sub>req</sub>
AFS ≥ FS <sub>req</sub>	1.77	≥ 1.61	1.17	< 1.58
<b>Probabilistic</b> <sup>(b)</sup>	FS <sub>pr</sub>	FS <sub>pr</sub> <sup>req</sup>	FS <sub>pr</sub>	FS <sub>pr</sub> <sup>req</sup>
FS <sub>pr</sub> ≥ FS <sub>pr</sub> <sup>req</sup>	1.26	≥ 1.0	1.0	≥ 1.0

<sup>(a)</sup> **RBSF AFS** computations with bounded PDF and  $k_R = 1.39$ .

<sup>(b)</sup> Reference value from probabilistic analyses is 90 m. FS<sub>pr</sub> is defined by the inverse of the demand/capacity ratio.

Deterministic and semi-probabilistic formats do not allow to account for uncertainties in parameters used for computations. The allowable  $H_w$  were especially high using mean values as strength parameters (102 m and 104 m an allowable capacity approximately 30% larger than the reference value). Using lower bound or 5% fractile values as strength parameters in a sensitivity analysis yielded much smaller  $H_w$  (82 m and 83 m), because of the large scatter in test data.

Application of **RBSF AFS** method (computation of FS<sub>req</sub> and AFS) allows to quantify uncertainties in the safety evaluation. Comparing (μ<sub>R</sub>/μ<sub>L</sub>) to FS<sub>req</sub> is then a mathematically expressible safe/unsafe criterion. Allowable  $H_w$  were 94 m and 86 m for bounded PDF with  $k_R$  respectively equal to 1.39 and 2. This criterion yielded the same  $H_w$  as probabilistic MC



simulations using variable R and bounded at 5% fractile. This is because direct integration used in computation of  $FS_{req}$  and MC simulations give the same  $p_f$ . While using  $(\mu_R/\mu_L) \geq FS_{req}$ ,  $H_w$  is 94 m corresponding to a D/C of 1.1 using the 90 m reference value. A maximum difference of 10%, as compared to the reference solution, is deemed acceptable for a simplified method. This difference decreases while increasing the PDF bound such that ~~RBSF~~ **AFS** is found to have the same range of applicability as that of MC with a maximum difference of the order of 10%. The criterion " $AFS \geq 1$ " gave also 94 m and 86 m for bounded PDF and  $k_R$  equal to 1.39 and 2, respectively. The range of applicability of the criterion " $AFS \geq 1$ " is indicated in terms of D/C ratios in Figure 13. If we accept a difference of 10% with the reference solution, the use of " $AFS \geq 1$ " is restricted to  $k_R$  value smaller than 2.5. On the other hand, comparing AFS to  $FS_{req}$  allows to introduce an additional safety margin. This added safety margin obviously yields to significantly lower allowable  $H_w$  and smaller D/C ratios as compared to other safety formats.




Figure 13. Demand/Capacity ratios for ~~RBSF~~ **AFS** as compared to MC, for varying PDF bounds in MC simulations ( $m_l$ ) and ~~RBSF~~ **AFS** ( $k_R$ )

From a practical standpoint, we feel confident to allow  $H_w$  equal to 83 m (3 m of overtopping) for the ICOLD Benchmark dam, using the " $AFS \geq FS_{req}$ " ~~RBSF~~ criterion with  $k_R = 1.39$  corresponding to the 5% fractile of the shear strength parameters. After performing the "sophisticated" analyses presented in this paper, we checked our findings from McCann et al. (1985) against rules of thumb for the allowable depth of overtopping,  $h_o$ , as a function of the dam height, using  $h = 80$  m (262.4 ft), in our case. Preliminary screening values for  $h_o$  are based on field experience and engineering judgement. They were recommended using the following description and equations (in feet) (i) for dams in good condition: with very little seepage, no cracks or movement ( $h_o = h^{0.6} \approx 8.6$  m), (ii) for dams in a fair condition: with moderate seepage, small structural cracks, slight differential movement ( $h_o = h^{0.45} - 1 \approx 3.5$  m) and (iii) for dams in poor conditions: with excessive seepage, large continuous cracks, excessive differential movements ( $h_o = h^{0.3} - 1 \approx 1$  m). The proposed ~~RBSF~~ " $AFS \geq FS_{req}$ " criterion yielded a  $h_o$  value of 3 m corresponding to the rule of thumb for a dam in fair condition. This sounds about right considering the potential scour at the downstream toe, the vibrations induced by the overflowing aerated water nappe, the increased in downstream toe uplift pressure due to the downstream face water jet changing direction at the toe. Such phenomenon are not being considered explicitly in dam safety guidelines, and are very difficult to model from a sound probabilistic standpoint.

## 6. Conclusions

In this paper, the consideration of material uncertainties in gravity dam sliding stability assessment was investigated for four safety evaluation formats: (i) deterministic, (ii) semi-

probabilistic (partial coefficient), (iii) reliability-based Adjustable Factor of Safety (AFS), and (iv) probabilistic Monte Carlo (MC) analysis. The results were presented in terms of the allowable water level,  $H_w$ , demand/capacity ratios (D/C), and FS to reach an unstable condition. In AFS and MC, the selected target failure probability,  $p_f^*$ , was  $10^{-5}$ . A 80 m-high gravity dam was used for applications without considering uncertainties in the applied loads,  $L$ . The main conclusions can be summarised as follows:

- The dam engineering profession shows a huge interest in **comprehensive** probabilistic methods. However, computation of  $p_f$  is very sensitive to the selection of shear strength random variables and PDF data as shown by the wide dispersion observed from the ICOLD Benchmark's results for a 80 m-high gravity dam. Practical applications are thus challenging, and generalisation of probabilistic analyses needs clear guidance.
- Using the deterministic format,  $H_w$  was found to be 103 m as compared to a reference MC solution with  $H_w$  equal to 90 m. The Deterministic safety format was found inadequate to introduce uncertainties even with an arbitrary reduction of the required FS if material tests are conducted
- In MC analyses, PDF bound data are the predominant parameters affecting the computation of  $p_f$ . A simplified bounded MC solution, using a single force resultant shear strength random variable,  $R$ , yielded a dam capacity approximately 10% larger than a bounded reference MC solution using two random variables (cohesion,  $C$  and friction,  $\tan\phi$ ). This excessive capacity decreases as the PDF bound becomes larger, the difference becoming insignificant when unbounded distributions are considered.
- A reliability-based **adjustable** safety factor (**RBFS** AFS) is a simplified and practical approach to introduce probabilistic uncertainties in shear strength parameters. The

1  
2  
3 criterion " $(\mu_R/\mu_L) \geq FS_{req}$ ", using direct integration to compute  $FS_{req}$ , yielded the same  
4  
5 results as MC simulations using the same PDF data and a single random variable, R.  
6  
7 This criterion is recommended as a preliminary substitute to full probabilistic MC  
8  
9 analysis that may therefore be avoided within the scope of the gravity dam stability  
10  
11 problem studied herein. The proposed simplified approach yields a good accuracy with  
12  
13 a 10% maximum difference with respect to a more comprehensive MC reference  
14  
15 solution. The criterion " $AFS \geq FS_{req}$ ", which introduces an additional safety margin,  
16  
17 cannot be compared the MC reference solution, because no additional safety margin  
18  
19 was introduced in the MC solution. " $AFS \geq FS_{req}$ " yielded a lower allowable water level  
20  
21 (83 m) than the MC solution (90 m). However,  $H_w = 83$  m does correspond to an  
22  
23 established rule of thumb to estimate the capacity of a 80 m-high gravity dam.  
24  
25  
26  
27  
28

- 29 • The proposed ~~RBSF~~ **AFS method** is a practical answer to the need for a simplified and  
30  
31 robust method to introduce material data shear strength uncertainties using a rigorous  
32  
33 approach in gravity dam stability analysis. Its range of applicability and the adequacy  
34  
35 of the safety margin provided as compared to reference MC solutions make ~~RBSF~~ **AFS**  
36  
37 a useful tool to use in sensitivity analysis of PDF data before undertaking more  
38  
39 comprehensive MC analyses (or variants such as FORM).  
40  
41  
42  
43  
44  
45  
46  
47

## 48 Acknowledgements

49  
50 The financial support provided by the Natural Science and Engineering Research Council  
51  
52 of Canada is acknowledged. The authors would also like to thank Dr Harald Kreuzer for  
53  
54 proposing the ~~RBSF~~ **AFS** and the fruitful technical discussions that took place during this  
55  
56 study.  
57  
58  
59  
60

References

Altarejos-Garcia, L., Escuder-Bueno, I., and Morales-Torres, A. (2015). "Advances on the failure analysis of the dam-foundation interface of concrete dams." *Materials*, 8, 8255-8278.

Altarejos-Garcia, L., Escuder-Bueno, I., Serrano-Lombillo, A., and Membrillera-Ortuño, G. D. (2012). "Methodology for estimating the probability of failure by sliding in concrete gravity dams in the context of risk analysis." *Structural Safety*, 36-37, 1-13.

ANCOLD. (2013). *Guidelines on design criteria for concrete gravity dams*. Australia: Australian National Committee on Large Dams.

ANCOLD. (1991). *Guidelines on design criteria for concrete gravity dams*. Australia: ANCOLD.

Baecher, G. B. (2016). "Uncertainty in dam safety risk analysis." *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*, 10(2), 92-108.

Bowles, D. S. (2007). "Tolerable risk for dams: How safe is safe enough?" Paper presented at the 27<sup>th</sup> US Society on Dams Annual Conference, Philadelphia, USA.

Bury, K. V., and Kreuzer, H. (1985). "Assessing the failure probability of gravity dams." *Water Power & Dam Construction*, 37(11), 46-50.

Carjaval, C., Peyras, L., Arnaud, P., Boissier, D., and Royet, P. (2009a). "Assessment of hydraulic load acting on dams including filling variability and stochastic simulations." *European Journal of Environmental and Civil Engineering*, 13(4), 399-411.

Carjaval, C., Peyras, L., Arnaud, P., Boissier, D., and Royet, P. (2009b). "Probabilistic modeling of floodwater level for dam reservoirs." *Journal of Hydrologic Engineering*, 14(3), 223-232.

Carjaval, C., Peyras, L., and Bacconnet, C. (2010). "On the loading/shear strength coupling in the probabilistic formulation of the limit-state in shear for gravity dams." *European Journal of Environmental and Civil Engineering*, 14(3), 283-301.

Carjaval, C., Peyras, L., Bacconnet, C., and Bécue, J.-P. (2009c). "Probability modelling of shear strength parameters of RCC gravity dams for reliability analysis of structural safety." *European Journal of Environmental and Civil Engineering*, 13(1), 91-119.

CDA. (2007). *Dam safety guidelines*. Edmonton, Canada: Canadian Dam Association.

CFBR. (2013). *Recommendations for the justification of the stability of gravity dams*. France: Comité Français des Barrages et Réservoirs.

CFBR. (2015). *Guidelines for the justification of embankment dams and levees*. France: CFBR.

Ebeling, R. M., Fong, M. T., Wibowo, J. L., and Chase, A. (2012). *Fragility analysis of a concrete gravity dam embedded in rock and its system response curve computed by the analytical program GDLAD\_Foundation*. Engineer Research and Development Center Technical Report ERDC TR-12-4. Pittsburgh, USA: United States Army Corps of Engineers.

Ellingwood, B., and Tekie, P. B. (2001). "Fragility analysis of concrete gravity dams." *Journal of Infrastructure Systems*, 7(2), 41-48.

Escuder-Bueno, I., Altarejos-Garcia, L., and Serrano-Lombillo, A. (2011). "Theme C - Estimation of the probability of failure of a gravity dam for the sliding failure mode." Paper presented at the XI ICOLD International Benchmark Workshop on Numerical Analysis of Dams, Valencia, Spain.

Escuder-Bueno, I., Mazzà, G., Morales-Torres, A., and Castillo-Rodriguez, J. T. (2016). "Computational aspects of dam risk analysis: findings and challenges." *Engineering*, 2(3), 319-324.

FERC. (2002). *Engineering guidelines for the evaluation of hydropower projects*. Washington DC, USA: Federal Energy Regulatory Commission.

FERC. (2014). *Risk-Informed Decision Making*. Washington DC, USA: FERC.

Fishman, Y.A. (2009). "Stability of concrete retaining structures and their interface with rock foundations." *International Journal of Rock Mechanics and Mining Sciences*, 46, 957-966.

Hartford, D. N. D., and Baecher, G. B. (2004). *Risk and uncertainty in dam safety*. London, UK: Thomas Telford.

Hartford, D. N. D., Baecher, G. B., Zielinski, P. A., Patev, R. C., Romanas, A., and Rytters, K. (2016). *Operational safety of dams and reservoirs - Understanding the reliability of flow-control systems*. London, UK: ICE Publishing.

Holický, M. (2009). *Reliability analysis for structural design*. Stellenbosch, South Africa: SUN MeDIA Publishing.

IS. (1984-1998). *Criteria for design of solid gravity dams*. New Delhi, India: Indian Standards.

Johansson, F., Westberg Wilde, M., Altarejos-García L. (2017). "Theme D, Risk Analysis—assessment of reliability for concrete dams." XIV ICOLD International Benchmark Workshop on Numerical Analysis of Dams, Stockholm, Sweden.

Jongejan, R. B., and Calle, E. O. F. (2013). "Calibrating semi-probabilistic safety assessments rules for flood defences. " *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*. doi:10.1080/17499518.2013.790731

Jongejan, R. B., and Maaskant, B. (2013). "The use of quantitative risk analysis for prioritizing flood risk management actions in the Netherlands." Paper presented at the 2013 CDA Annual Conference, Montreal, Canada.

Kalinina, A., Spada, M., Marelli, S., Burgherr, P., and Sudret, B. (2016). *Uncertainties in the risk assessment of hydropower dams - State-of-the-art and outlook*. Technical report. Zürich, Switzerland: ETH.

Kovarik, J.-B. (2000). "What is a safety factor in civil engineering? (in French: "Qu'est-ce qu'un coefficient de sécurité en génie civil ?")." *Revue Française de Génie Civil*, 4(6), 607-651.

Kreuzer, H. (2000). "Risk analysis for existing dams: merits and limits of credibility." *Hydropower & Dams*, 7(1), 49-53.

Kreuzer, H. (2003). "Uncertainty in the assessment of failure probabilities." *Hydropower & Dams*, 10(6), 98-101.

Kreuzer, H., and Léger, P. (2013). "The Adjustable Factor of Safety: A reliability-based approach to assess the factor of safety for concrete dams." *Hydropower & Dams*, 20(1), 67-90.

Krounis, A., and Johansson, F. (2012). "The influence of correlation between cohesion and friction angle on the probability of failure for sliding of concrete dams." In Escuder-Bueno. et al. (Ed.), *Risk Analysis, Dam Safety, Dam Security and Critical Infrastructure Management*. London: Taylor & Francis Group.

Krounis, A., Johansson, F., Spross, J., and Larsson, S. (2016). "Influence of cohesive strength in probabilistic sliding stability reassessment of concrete dams." *Journal of Geotechnical and Geoenvironmental Engineering*. doi:10.1061/(ASCE)GT.1943-5606.0001583

Lombardi, G. (1988). "Logarithmic double-bounded distribution (in French: "Distribution à double borne logarithmique")." Paper presented in the 16<sup>th</sup> ICOLD Congress, San Francisco, Q.63, R.17, pp.1337-1348, USA.

Lombardi, G. (1993). "Concrete dams and their foundation - Evaluation for static loading." Paper presented at the International Workshop on Dam Safety Evaluation, Grindelwald, Switzerland. Vol.4, 77-90.

Lombardi, G. (2006). "Tendencies, probabilities and risk analysis for dams." *Dam Engineering*, 17(1), 5-29.



Luhmann, N. (2005). *Risk - A sociological theory*. London, UK: Aldine Transaction Publisher.

McCann, M.W., Franzini, J.B., Kavazanjian, E., Shah, H.C. 1985. *Preliminary safety evaluation of existing dams*, Vol. I, Report No. 69, Department of Civil Engineering, Stanford University.

Morin, S. (2016). R-AFS Version 1.6. Ecole Polytechnique de Montréal.

Peyras, L., Carjaval, C., Felix, H., Bacconnet, C., Royet, P., and Boissier, D. (2012). "Probability-based assessment of dam safety using combined risk analysis and reliability methods – Application to hazards studies." *European Journal of Environmental and Civil Engineering*, 16(7), 795-817.

Peyras, L., Royet, P., Deroo, L., Albert, R., Becue, J.-P., Aigouy, S., Bourdarot, E, Loudiere, D., and Kovarik, J.-B. (2008). "French recommendations for limit-state analytical review of gravity dam stability." *European Journal of Environmental and Civil Engineering*, 12(9-10), 1137-1164.

Porter, K. (2017). *A beginner's guide to fragility, vulnerability, and risk*. University of Colorado Boulder.

Riley, K., Webley, P., and Thomson, M. (2017). *Natural hazard uncertainty assessment: Modeling and decision support* (Vol. 223). Hoboken, USA: John Wiley & Sons.

Rocha, M. (1974). *Present possibilities of studying foundations of concrete dams*. Paper presented at the Third Congress of the International Society of Rock Mechanics, Denver, USA.

Ruggeri, G. (2004). *Sliding safety of existing gravity dams - Final report*: ICOLD European Club.

SPANCOLD. (2003). *Dam safety technical guidelines N°2: Criteria for dams and associated works projects (in Spanish: "Guía Técnicas de Seguridad de Presas N° 2: Criterios para proyectos de presas y sus obras anejas")*. Madrid, Spain: Spanish Committee on Large Dams.

SPANCOLD. (2013). *Risk analysis applied to management of dam safety*. Madrid, Spain: SPANCOLD.

Spross, J., Johansson, F., and Larsson, S. (2013). "On the use of pore pressure measurements in safety reassessments of concrete dams founded on rock." *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*, 8(2), 117-128.



Tekie, P. B. (2002). *Fragility Analysis of Concrete Gravity Dams*. USACE ERDC Technical Report TR-02-6. Washington DC, USA: USACE.

The MathWorks, I. (2016). MATLAB R2016a.

USACE. (2005). *Stability analysis of concrete structures*. Washington DC, USA: USACE.

USACE. (1995). *Gravity dam design*. Washington DC, USA: USACE.

USBR. (1976). *Design of gravity dams*. Denver, USA: United States Bureau of Reclamation.

Vergouwe, R. (2016). *The national flood risk analysis for the Netherlands. Final report*. The Netherlands: Rijkswaterstaat VNK Project Office.

Westberg Wilde, M., and Johansson, F. (2013). "System reliability of concrete dams with respect to foundation stability: Application to a spillway." *Journal of Geotechnical and Geoenvironmental Engineering*, 139(2), 308-319.

Westberg Wilde, M., and Johansson, F. (2016). *Probabilistic model code for concrete dams*. Report 2016:292. Stockholm, Sweden: Energiforsk.

Zhang, L., Peng, M., Chang, D., and Xu, Y. (2016). *Dam failure mechanisms and risk assessment*. Singapore: John Wiley & Sons.

**Appendix 1 – ICOLD Benchmark material data**

The fifteen couples of friction angle  $\phi$  (°) and cohesion C (kPa) specified as input "material test" data in the 11th ICOLD Numerical Benchmark (Escuder-Bueno, Altarejos-Garcia and Serrano-Lombillo 2011) are:  $(\phi, C) = \{(45, 500); (37, 300); (46, 300); (45, 700); (49, 800); (53, 200); (54, 600); (45, 0); (49, 100); (60, 200); (63, 200); (62, 400); (60, 700); (56, 100); (62, 400)\}$ .